

1° Géométrie: suivant plan

SCOE.01.0010

Geometry: See drawing

2° Caractéristiques initiales

Primary Technical Properties: (before test)

Tension et limites:		90V/20	150V/20	200V/20	230V/10	230V/15
Tension and limits:						
Tension statique:	E-M 100V/s	72V-108V	120V-180V	160V-240V	207V-253V	195V-265V
DC Spark over Voltage:	E-E	100/200	200/400	300/500	320/460	300/500
Tension dynamique:	E-M					
Impulse Spark over Voltage:	1kV/μs	≤640V	≤640V	≤750V	≤750V	≤750V
Résistance isolement:	≤90V ≥90V	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ
Insulation Resistance:	50V DC 100V DC					
Capacité:	E-M 1MHz	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF
Capacitance:	E-E	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF
Tension d extinction:	RC//:150Ω-100nF;RS=330Ω	≥70V	≥80V	≥80V	≥80V	≥80V
Holdover Voltage	U(I)600V DC;1.5A;50cycle;E-M					
Tension de lueur:		≤100V	≤100V	≤100V	≤100V	≤100V
Glow Voltage:						
Courant de transition lueur/arc		0.5A	0.5A	0.5A	0.5A	0.5A
Glow to arc transition current:						
Tension d arc		≤25V	≤25V	≤25V	≤25V	≤25V
Arc Voltage:						

3° Pouvoir d écoulement: (après tests)

Power-flow Properties: (after life test)

Tension statique:	E-M 100V/s	72V-108V	120V-180V	160V-240V	207V-253V	195V-265V
DC Spark over Voltage:	E-E	100/200	200/400	300/500	320/460	300/500
Tension dynamique:		≤640V	≤640V	≤750V	≤750V	≤750V
Impulse Spark over Voltage:						
Résistance isolement:		≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ
Insulation Resistance:						
Décharge Alternative	50/60Hz,600V E-M	10A	10A	10A	10A	10A
AC discharge current:	5times,1s interval 3min E1/E2-M	20A	20A	20A	20A	20A
Décharge Impulsionnelle	8/20μs,+5/-5 E-M	10kA	10kA	10kA	10kA	10kA
Impulse discharge current:	interval 3min E1/E2-M	20kA	20kA	20kA	20kA	20kA
Décharge Impulsionnelle	8/20μs	25kA	25kA	25kA	25kA	25kA
Impulse discharge current:	1time					
Décharge Impulsionnelle	10/350μs E-M	2KA	2KA	2KA	2KA	2KA
Impulse discharge current:	1time E1/E2-M	4KA	4KA	4KA	4KA	4KA
Décharge Impulsionnelle	10/1000μs	100A	100A	100A	100A	100A
Impulse life:	300times,interval 2min					

4° Code:


Part number:

	9293001	9293002	9293005	9293062	9293007
QVGQ2.E184939	YES	YES	YES	YES	YES
	YES			YES	YES
REG.-Nr.40008209					

1. solderability: see CEI 68-2-20

2. This product is 2002/95/EC directive (ROHS); all test are ITU-T K.12 compliant.

Date	Code N°
2009-5-15	92 930 XX XX



1° Géométrie: suivant plan

SCOE.01.0010

Geometry: See drawing

2° Caractéristiques initiales

Primary Technical Properties: (before test)

Tension et limites:		230V/20	250V/12	250V/20	260V/20	350V/15
Tension and limits:						
Tension statique:	E-M 100V/s	184V-276V	220V-280V	200V-300V	208V-312V	298V-402V
DC Spark over Voltage:	E-E	300/500	400/600	400/600	400/600	500/700
Tension dynamique:	E-M	≤750V	≤750V	≤750V	≤750V	≤900V
Impulse Spark over Voltage:	1kV/μs					
Résistance isolement:	≤90V ≥90V	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ
Insulation Resistance:	50V DC 100V DC					
Capacité:	E-M 1MHz	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF
Capacitance:	E-E	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF
Tension d extinction:	RC//:150Ω-100nF;RS=330Ω	≥80V	≥80V	≥80V	≥80V	≥80V
Holdover Voltage:	U(I)600V DC;1.5A;50cycle;E-M					
Tension de lueur:		≤100V	≤100V	≤100V	≤100V	≤100V
Glow Voltage:						
Courant de transition lueur/arc		0.5A	0.5A	0.5A	0.5A	0.5A
Glow to arc transition current:						
Tension d arc		≤25V	≤25V	≤25V	≤25V	≤25V
Arc Voltage:						

3° Pouvoir d écoulement: (après tests)

Power-flow Properties: (after life test)

Tension statique:	E-M 100V/s	184V-276V	220V-280V	200V-300V	208V-312V	298V-402V
DC Spark over Voltage:	E-E	300/500	400/600	400/600	400/600	500/700
Tension dynamique:		≤750V	≤750V	≤750V	≤750V	≤900V
Impulse Spark over Voltage:						
Résistance isolement:		≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ
Insulation Resistance:						
Décharge Alternative	50/60Hz,600V E-M	10A	10A	10A	10A	10A
AC discharge current:	5times,1s interval 3min E1/E2-M	20A	20A	20A	20A	20A
Décharge Impulsionnelle	8/20μs,+5/-5 E-M	10kA	10kA	10kA	10kA	10kA
Impulse discharge current:	interval 3min E1/E2-M	20kA	20kA	20kA	20kA	20kA
Décharge Impulsionnelle	8/20μs	25kA	25kA	25kA	25kA	25kA
Impulse discharge current:	1time					
Décharge Impulsionnelle	10/350μs E-M	2kA	2kA	2kA	2kA	2kA
Impulse discharge current:	1time E1/E2-M	4kA	4kA	4kA	4kA	4kA
Décharge Impulsionnelle	10/1000μs	100A	100A	100A	100A	100A
Impulse life:	300times,interval 2min					

4° Code:


Part number:

	9293057	9293009	9293059	9293010	9293065
QVGG2.E184939	YES	YES	YES	YES	YES
	YES				YES
REG.-Nr.40008209					

1. solderability: see CEI 68-2-20

2. This product is 2002/95/EC directive (ROHS); all test are ITU-T K.12 compliant.

Date	Code N°
2009-5-15	92 930 XX XX



1° Géométrie: suivant plan

SCOE.01.0010

Geometry: See drawing

2° Caractéristiques initiales

Primary Technical Properties: (before test)

Tension et limites:		350V/20	400V/20	450V/20	470V/20	500V/20
Tension and limits:						
Tension statique:	E-M 100V/s	280V-420V	320V-480V	360V-540V	376V-564V	400V-600V
DC Spark over Voltage:	E-E	500/700	600/1000	800/1000	800/1000	800/1100
Tension dynamique:	E-M	≤900V	≤1000V	≤1100V	≤1100V	≤1100V
Impulse Spark over Voltage:	1kV/μs					
Résistance isolement:	≤90V ≥90V	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ	≥10GΩ
Insulation Resistance:	50V DC 100V DC					
Capacité:	E-M 1MHz	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF	≤0.9pF
Capacitance:	E-E	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF	≤0.5pF
Tension d extinction:	RC//:150Ω-100nF;RS=330Ω	≥80V	≥80V	≥80V	≥80V	≥80V
Holdover Voltage	U(I)600V DC;1.5A;50cycle;E-M					
Tension de lueur:		≤100V	≤100V	≤100V	≤100V	≤100V
Glow Voltage:						
Courant de transition lueur/arc		0.5A	0.5A	0.5A	0.5A	0.5A
Glow to arc transition current:						
Tension d arc		≤25V	≤25V	≤25V	≤25V	≤25V
Arc Voltage:						



3° Pouvoir d écoulement: (après tests)

Power-flow Properties: (after life test)

Tension statique:	E-M 100V/s	280V-420V	320V-480V	360V-540V	376V-564V	400V-600V
DC Spark over Voltage:	E-E	500/700	600/1000	800/1000	800/1000	800/1100
Tension dynamique:		≤900V	≤1000V	≤1100V	≤1100V	≤1100V
Impulse Spark over Voltage:						
Résistance isolement:		≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ	≥1000MΩ
Insulation Resistance:						
Décharge Alternative	50/60Hz,600V E-M	10A	10A	10A	10A	10A
AC discharge current:	5times,1s interval 3min E1/E2-M	20A	20A	20A	20A	20A
Décharge Impulsionnelle	8/20μs,+5/-5 E-M	10kA	10kA	10kA	10kA	10kA
Impulse discharge current:	interval 3min E1/E2-M	20kA	20kA	20kA	20kA	20kA
Décharge Impulsionnelle	8/20μs	25kA	25kA	25kA	25kA	25kA
Impulse discharge current:	1time					
Décharge Impulsionnelle	10/350μs E-M	2kA	2kA	2kA	2kA	2kA
Impulse discharge current:	1time E1/E2-M	4kA	4kA	4kA	4kA	4kA
Décharge Impulsionnelle	10/1000μs	100A	100A	100A	100A	100A
Impulse life:	300times,interval 2min					

4° Code:


Part number:

	9293015	9293016	9293020	9293021	9293022
QVQG2.E184939	YES	YES	YES	YES	YES
	YES			YES	
REG.-Nr.40008209					

1. solderability: see CEI 68-2-20

2. This product is 2002/95/EC directive(ROHS);all test are ITU-T K.12 compliant.

Date	Code N°
2009-5-15	92 930 XX XX




CITEL
BT R

1° Géométrie: suivant plan

SCOE.01.0010

Geometry: See drawing

2° Caractéristiques initiales

Primary Technical Properties: (before test)

Tension et limites:		550V/15	600V/-15+20
Tension and limits:			
Tension statique:	E-M 100V/s	468V-632V	510V-720V
DC Spark over Voltage:	E-E	900/1200	850/1250
Tension dynamique:	E-M	≤ 1200V	≤ 1200V
Impulse Spark over Voltage:	1kV/μs		
Résistance isolement:	≤ 90V ≥ 90V	≥ 10GΩ	≥ 10GΩ
Insulation Resistance:	50V DC 100V DC		
Capacité:	E-M 1MHz	≤ 0.9pF	≤ 0.9pF
Capacitance:	E-E	≤ 0.5pF	≤ 0.5pF
Tension d extinction:	RC//:150Ω-100nF;RS=330Ω	≥ 80V	≥ 80V
Holdover Voltage	U(I)600V DC;1.5A;50cycle;E-M		
Tension de lueur:		≤ 100V	≤ 100V
Glow Voltage:			
Courant de transition lueur/arc		0.5A	0.5A
Glow to arc transition current:			
Tension d arc		≤ 25V	≤ 25V
Arc Voltage:			

3° Pouvoir d écoulement: (après tests)

Power-flow Properties: (after life test)

Tension statique:	E-M 100V/s	468V-632V	510V-720V
DC Spark over Voltage:	E-E	900/1200	850/1250
Tension dynamique:		≤ 1200V	≤ 1200V
Impulse Spark over Voltage:			
Résistance isolement:		≥ 1000MΩ	≥ 1000MΩ
Insulation Resistance:			
Décharge Alternative	50/60Hz,600V E-M	10A	10A
AC discharge current:	5times,1s interval 3min E1/E2-M	20A	20A
Décharge Impulsionnelle	8/20μs,+5/-5 E-M	10kA	10kA
Impulse discharge current:	interval 3min E1/E2-M	20kA	20kA
Décharge Impulsionnelle	8/20μs	25kA	25kA
Impulse discharge current:	1time		
Décharge Impulsionnelle	10/350μs E-M	2KA	2KA
Impulse discharge current:	1time E1/E2-M	4KA	4KA
Décharge Impulsionnelle	10/1000μs	100A	100A
Impulse life:	300times,interval 2min		

4° Code:

9293075 9293026

Part number:



QVGQ2.E184939



REG.-Nr.40008209

YES

1. solderability: see CEI 68-2-20

2. This product is 2002/95/EC directive(ROHS);all test are ITU-T K.12 compliant.

Date	Code N°
2009-5-15	92 930 XX XX