





# CITEL

## UL497B LISTED - I<sub>max</sub> 20kA - I<sub>n</sub> 5kA - Modular


### DLAH-170



- Hybrid Technology
- UL497B LISTED
- 20kA I<sub>max</sub> (1x 8/20us)
- 5kA I<sub>imp</sub> (2x 10/350us)
- 5kA I<sub>n</sub> (10x 8/20us)
- 2.4A Max. Load Current
- Modular
- 2W+SHIELD+G



**G: 3-electrode gas tube**  
**Gb: 2-electrode gas tube**  
**L: Inductor**  
**D: Clamping diode**



Electrical Characteristics		
Network		RTC, ADSL2, VDSL2
Nominal line voltage	U <sub>n</sub>	150 V
Max. DC operating voltage	U <sub>c</sub>	170 Vdc
Cut-off frequency -3dB, 100 ohm system	f max.	> 1.8 MHz
Cut-off frequency -1dB, 100 ohm system	f max.	> 1 MHz
Max. load current @25°C	I <sub>L</sub>	2.4 A
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	20 kA
Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category	I <sub>n</sub> L/PE	5 kA
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)	U <sub>p</sub>	220 V
Protection Level C3 (10/1000μs), 300 applications@10 A, Y-C (Line/Earth)	U <sub>p</sub>	220 V
Impulse current D1 (10/350μs), 2 applications, X-C (Line/Earth)	I <sub>imp</sub>	5 kA
Mechanical Characteristics		
Technology		GDT+TVS diode
Connection to Network		By screw terminal: cross section 0.4-1.5mm <sup>2</sup>
Format		Plug-in DIN box
Mounting		Symmetrical rail 35 mm (EN 60715)
Operating temperature	T <sub>u</sub>	-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit
NETWORK CONFIGURATION		1 pair
MOUNTING		DIN RAIL
MATERIAL		Thermoplastic UL94-V0
SPARE PART		DLAHM-170D3
Standards		
Certification		UL Listed
Environmental standards		EU RoHS
UL STANDARD		UL497B
UL CATEGORY		QVGQ
UL FILE NUMBER		E184939
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
Part number		
<b>641005</b>		

