



- Hybrid MOV-GSG Technology
- UL1449 Type 2 LISTED
- 50kA Surge Current Rating per mode
- Extended life with no leakage current
- Visual LED fault indicator and audible alarm
- NEMA 6 (exceeds NEMA 4X or 4)
- UL1283 Filter
- 10-Year warranty

	Electrical Characteristics																																																										
	<table border="1"> <tbody> <tr><td>POWER SPD TYPE</td><td></td><td>UL1449 TYPE 2 LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>600</td></tr> <tr><td>AC/DC/DC PV/RF</td><td></td><td>AC</td></tr> <tr><td>PHASE</td><td>(PH)</td><td>3D</td></tr> <tr><td>AMPS</td><td>(A)</td><td>N/A</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-35</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+80</td></tr> <tr><td>MODES</td><td></td><td>L-L, L-G</td></tr> <tr><td>VPR</td><td>(V)</td><td>3000/-/1800/-</td></tr> <tr><td>MCOV</td><td>(V)</td><td>690/690/-/-</td></tr> <tr><td>IN</td><td>(kA)</td><td>20</td></tr> <tr><td>15 impulses 8/20µs</td><td></td><td></td></tr> <tr><td>SCCR</td><td>(kA)</td><td>200</td></tr> <tr><td>IMAX</td><td>(kA)</td><td>50</td></tr> <tr><td>8/20µs</td><td></td><td></td></tr> </tbody> </table>	POWER SPD TYPE		UL1449 TYPE 2 LISTED	VOLTS	(V)	600	AC/DC/DC PV/RF		AC	PHASE	(PH)	3D	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODES		L-L, L-G	VPR	(V)	3000/-/1800/-	MCOV	(V)	690/690/-/-	IN	(kA)	20	15 impulses 8/20µs			SCCR	(kA)	200	IMAX	(kA)	50	8/20µs															
POWER SPD TYPE		UL1449 TYPE 2 LISTED																																																									
VOLTS	(V)	600																																																									
AC/DC/DC PV/RF		AC																																																									
PHASE	(PH)	3D																																																									
AMPS	(A)	N/A																																																									
AMBIENT MIN	(C)	-35																																																									
AMBIENT MAX	(C)	+80																																																									
MODES		L-L, L-G																																																									
VPR	(V)	3000/-/1800/-																																																									
MCOV	(V)	690/690/-/-																																																									
IN	(kA)	20																																																									
15 impulses 8/20µs																																																											
SCCR	(kA)	200																																																									
IMAX	(kA)	50																																																									
8/20µs																																																											
	Installation																																																										
	<table border="1"> <tbody> <tr><td>Operating Temperature_{Min}</td><td>°C</td><td>-40.0000</td></tr> <tr><td>Operating Temperature_{Max}</td><td>°C</td><td>85.0000</td></tr> <tr><td>Operating Temperature_{Min}</td><td>°F</td><td>-40.0000</td></tr> <tr><td>Operating Temperature_{Max}</td><td>°F</td><td>85.0000</td></tr> <tr><td>Operating Relative Humidity_{Max}</td><td>%RH</td><td>Can be submerged</td></tr> <tr><td>Operating Altitude_{Min}</td><td>Ft</td><td>2000.0000</td></tr> <tr><td>Operating Altitude_{Max}</td><td>Ft</td><td>6500.0000</td></tr> <tr><td>Housing/Enclosure material</td><td></td><td>Aluminum cast</td></tr> <tr><td>Mounting</td><td></td><td>Side mount</td></tr> <tr><td>IP Environmental rating/IP</td><td></td><td>IP66</td></tr> <tr><td>NEMA Environmental rating/NEMA</td><td></td><td>NEMA 6</td></tr> <tr><td>Installation Location</td><td></td><td>Indoor / outdoor</td></tr> <tr><td>Accessories</td><td></td><td>brackets</td></tr> <tr><td>Product Dimension_L</td><td>mm</td><td>102.0000</td></tr> <tr><td>Product Dimension_H</td><td>mm</td><td>62.0000</td></tr> <tr><td>Product Dimension_W</td><td>mm</td><td>88.0000</td></tr> <tr><td>Product Dimension_L</td><td>In</td><td>4.0160</td></tr> <tr><td>Product Dimension_H</td><td>In</td><td>2.4410</td></tr> <tr><td>Product Dimension_W</td><td>In</td><td>3.4650</td></tr> </tbody> </table>	Operating Temperature _{Min}	°C	-40.0000	Operating Temperature _{Max}	°C	85.0000	Operating Temperature _{Min}	°F	-40.0000	Operating Temperature _{Max}	°F	85.0000	Operating Relative Humidity _{Max}	%RH	Can be submerged	Operating Altitude _{Min}	Ft	2000.0000	Operating Altitude _{Max}	Ft	6500.0000	Housing/Enclosure material		Aluminum cast	Mounting		Side mount	IP Environmental rating/IP		IP66	NEMA Environmental rating/NEMA		NEMA 6	Installation Location		Indoor / outdoor	Accessories		brackets	Product Dimension _L	mm	102.0000	Product Dimension _H	mm	62.0000	Product Dimension _W	mm	88.0000	Product Dimension _L	In	4.0160	Product Dimension _H	In	2.4410	Product Dimension _W	In	3.4650	
Operating Temperature _{Min}	°C	-40.0000																																																									
Operating Temperature _{Max}	°C	85.0000																																																									
Operating Temperature _{Min}	°F	-40.0000																																																									
Operating Temperature _{Max}	°F	85.0000																																																									
Operating Relative Humidity _{Max}	%RH	Can be submerged																																																									
Operating Altitude _{Min}	Ft	2000.0000																																																									
Operating Altitude _{Max}	Ft	6500.0000																																																									
Housing/Enclosure material		Aluminum cast																																																									
Mounting		Side mount																																																									
IP Environmental rating/IP		IP66																																																									
NEMA Environmental rating/NEMA		NEMA 6																																																									
Installation Location		Indoor / outdoor																																																									
Accessories		brackets																																																									
Product Dimension _L	mm	102.0000																																																									
Product Dimension _H	mm	62.0000																																																									
Product Dimension _W	mm	88.0000																																																									
Product Dimension _L	In	4.0160																																																									
Product Dimension _H	In	2.4410																																																									
Product Dimension _W	In	3.4650																																																									
	Miscellaneous																																																										
	<table border="1"> <tbody> <tr><td>Individual Pack</td><td></td><td>Yes</td></tr> <tr><td>Storage Temperature_{Min}</td><td>°C</td><td>-40.0000</td></tr> <tr><td>Storage Temperature_{Max}</td><td>°C</td><td>85.0000</td></tr> <tr><td>Storage Temperature_{Min}</td><td>°F</td><td>-40.0000</td></tr> <tr><td>Storage Temperature_{Max}</td><td>°F</td><td>85.0000</td></tr> </tbody> </table>	Individual Pack		Yes	Storage Temperature _{Min}	°C	-40.0000	Storage Temperature _{Max}	°C	85.0000	Storage Temperature _{Min}	°F	-40.0000	Storage Temperature _{Max}	°F	85.0000																																											
Individual Pack		Yes																																																									
Storage Temperature _{Min}	°C	-40.0000																																																									
Storage Temperature _{Max}	°C	85.0000																																																									
Storage Temperature _{Min}	°F	-40.0000																																																									
Storage Temperature _{Max}	°F	85.0000																																																									
	Mechanical Characteristics																																																										
	<table border="1"> <tbody> <tr><td>TECHNOLOGY</td><td></td><td>MOV-GSG</td></tr> <tr><td>NETWORK CONFIGURATION</td><td></td><td>3PH, 3W+G, Delta</td></tr> <tr><td>CONNECTION METHOD</td><td></td><td>36" #12 AWG LEADS</td></tr> <tr><td>MOUNTING</td><td></td><td>SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)</td></tr> <tr><td>MATERIAL</td><td></td><td>Aluminum cast</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>6</td></tr> <tr><td>FAIL-SAFE BEHAVIOR</td><td></td><td>Yes, no upstream over current protection required</td></tr> <tr><td>REAL-TIME DIAGNOSTICS</td><td></td><td>LED and audible alarm</td></tr> <tr><td>DIMENSIONS</td><td></td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td></td><td>2.5 lbs.</td></tr> </tbody> </table>	TECHNOLOGY		MOV-GSG	NETWORK CONFIGURATION		3PH, 3W+G, Delta	CONNECTION METHOD		36" #12 AWG LEADS	MOUNTING		SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)	MATERIAL		Aluminum cast	NEMA RATING (IP RATING)		6	FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required	REAL-TIME DIAGNOSTICS		LED and audible alarm	DIMENSIONS		See diagram	WEIGHT		2.5 lbs.																												
TECHNOLOGY		MOV-GSG																																																									
NETWORK CONFIGURATION		3PH, 3W+G, Delta																																																									
CONNECTION METHOD		36" #12 AWG LEADS																																																									
MOUNTING		SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)																																																									
MATERIAL		Aluminum cast																																																									
NEMA RATING (IP RATING)		6																																																									
FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required																																																									
REAL-TIME DIAGNOSTICS		LED and audible alarm																																																									
DIMENSIONS		See diagram																																																									
WEIGHT		2.5 lbs.																																																									
	Standards																																																										
	<table border="1"> <tbody> <tr><td>UL STANDARD</td><td></td><td>UL1449 5th Edition</td></tr> <tr><td>UL CATEGORY</td><td></td><td>VZCA, VZCA7</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E326289</td></tr> <tr><td>STANDARDS</td><td></td><td>NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> </tbody> </table>	UL STANDARD		UL1449 5th Edition	UL CATEGORY		VZCA, VZCA7	UL FILE NUMBER		E326289	STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																														
UL STANDARD		UL1449 5th Edition																																																									
UL CATEGORY		VZCA, VZCA7																																																									
UL FILE NUMBER		E326289																																																									
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																									

ENVIRONMENTAL STANDARDS	ROHS
Part number	
750804	