



CITEL

TSP15M-P-48D3



- 1 Pair Protection
- Modes of Protection L-L,L-G
- Conduit Mounting-1/2 inch NPT
- Direct Transducer Mount
- Parallel or Series Connection Options
- BABA-Build America-Buy America Compliant

Electrical Characteristics		
VOLTS	(V)	48
MAXIMUM LINE VOLTAGE	(V)	54
WIRES		4W+GROUND
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-55
AMBIENT MAX	(C)	+85
PROTECTION LEVEL	(V)	82
IN 15 impulses 8/20 μ s	(kA)	10
IMAX 8/20 μ s	(kA)	15
Installation		
Operating Relative HumidityMax	%RH	Can be submerged
Operating AltitudeMax	Ft	6500.0000
Housing/Enclosure material		Stainless Steel
Mounting		Conduit-1/2" NPT
Installation Location		Indoor / outdoor
Product DimensionL	mm	114.3000
Product DimensionH	mm	26.0000
Product DimensionW	mm	27.9400
Product DimensionL	In	4.5000
Product DimensionH	In	1.0000
Product DimensionW	In	1.1000
Product Weight	lbs	0.8000
Miscellaneous		
Individual Pack		Yes
Mechanical Characteristics		
CONNECTION METHOD		Parallel- #16 AWG Copper Wires-Tinned
Part number		
6338		

