



- ✦ 1 Pair Protection
- ✦ Modes of Protection L-L,L-G
- ✦ Conduit Mounting-1/2 inch NPT
- ✦ Direct Transducer Mount
- ✦ Parallel or Series Connection Options

Electrical Characteristics			
VOLTS	(V)		48
MAXIMUM LINE VOLTAGE	(V)		54
WIRES			4W+GROUND
LINE CURRENT MAX	(A)		0.3
AMBIENT MIN	(C)		-55
AMBIENT MAX	(C)		+85
PROTECTION LEVEL	(V)		82
IN 15 impulses 8/20µs	(kA)		10
IMAX 8/20µs	(kA)		15
Installation			
Operating Relative HumidityMax	%RH		Can be submerged
Operating AltitudeMin	Ft		2000.0000
Operating AltitudeMax	Ft		6500.0000
Housing/Enclosure material			Stainless Steel
Mounting			Conduit-1/2" NPT
Installation Location			Indoor / outdoor
Product DimensionL	mm		114.3000
Product DimensionH	mm		26.0000
Product DimensionW	mm		27.9400
Product DimensionL	In		4.5000
Product DimensionH	In		1.0000
Product DimensionW	In		1.1000
Product Weight	lbs		0.8000
Miscellaneous			
Individual Pack			Yes
Mechanical Characteristics			
CONNECTION METHOD			Parallel- #16 AWG Copper Wires-Tinned
Part number			
6338			