





- ↳ Hybrid MOV-GSG Technology
- ↳ UL1449 Type 1 LISTED
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator and audible alarm
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ Optional Type 2 LISTED with UL1283 Filter
- ↳ 10-Year warranty

	<b>Características eléctricas</b>	
	POWER SPD TYPE	UL1449 TYPE 1 LISTED
	TENSION	(V) 240/120
	AC/DC/DC PV/RF	AC
	FASE	(PH) 1S
	AMPS	(A) N/A
	AMBIENT MIN	(C) -35
	AMBIENT MAX	(C) +80
	MODOS	L-L, L-N, L-G, N-G
	VPR	(V) 1200/700/1200/1200
	MCOV	(V) 280/140/140/120
	IN	(kA) 20
	Icc cortocircuito	(kA) 150
	IMAX	(kA) 50
	<b>Características mecánicas</b>	
	TECNOLOGIA	MOV-GSG
CONFIGURACION DE RED	1PH, 3W+G, Split Phase	
FORMA DE CONEXION	36" #12 AWG LEADS	
MONTAJE	BACK MOUNT, THREADED M22 (1/2" NPT ADAPTER)	
MATERIAL	Aluminum cast	
NEMA RATING (IP RATING)	6 (IP66)	
DESCONEXION SEGURA	Yes, no upstream over current protection required	
REAL-TIME DIAGNOSTICS	LED and audible alarm	
DIMENSIONS	See diagram	
WEIGHT	2.5 lbs.	
<b>Normas</b>		
UL STANDARD	UL1449 5th Edition	
UL CATEGORY	VZCA	
UL FILE NUMBER	E326289	
NORMAS	NOM-003-SCFI-2014, NOM-001-SCFI-1993	
ENVIRONMENTAL STANDARDS	ROHS	
<b>Código</b>		
751112		