



M50-240D-A



- ↳ Hybrid MOV-GSG Technology
- ↳ UL1449 Type 1 LISTED
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator and audible alarm
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ Optional Type 2 LISTED with UL1283 Filter
- ↳ 10-Year warranty

	Características eléctricas																																								
	<table border="1"> <tr> <td>POWER SPD TYPE</td> <td></td> <td>UL1449 TYPE 1 LISTED</td> </tr> <tr> <td>TENSION</td> <td>(V)</td> <td>240</td> </tr> <tr> <td>AC/DC/DC PV/RF</td> <td></td> <td>AC</td> </tr> <tr> <td>FASE</td> <td>(PH)</td> <td>3D</td> </tr> <tr> <td>AMPS</td> <td>(A)</td> <td>N/A</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-35</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+80</td> </tr> <tr> <td>MODOS</td> <td></td> <td>L-L, L-G</td> </tr> <tr> <td>VPR</td> <td>(V)</td> <td>1200/-/1200/-</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>280/280/-/-</td> </tr> <tr> <td>IN</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>I_{cc cortocircuito}</td> <td>(kA)</td> <td>150</td> </tr> <tr> <td>IMAX</td> <td>(kA)</td> <td>50</td> </tr> </table>		POWER SPD TYPE		UL1449 TYPE 1 LISTED	TENSION	(V)	240	AC/DC/DC PV/RF		AC	FASE	(PH)	3D	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODOS		L-L, L-G	VPR	(V)	1200/-/1200/-	MCOV	(V)	280/280/-/-	IN	(kA)	20	I _{cc cortocircuito}	(kA)	150	IMAX	(kA)	50
POWER SPD TYPE		UL1449 TYPE 1 LISTED																																							
TENSION	(V)	240																																							
AC/DC/DC PV/RF		AC																																							
FASE	(PH)	3D																																							
AMPS	(A)	N/A																																							
AMBIENT MIN	(C)	-35																																							
AMBIENT MAX	(C)	+80																																							
MODOS		L-L, L-G																																							
VPR	(V)	1200/-/1200/-																																							
MCOV	(V)	280/280/-/-																																							
IN	(kA)	20																																							
I _{cc cortocircuito}	(kA)	150																																							
IMAX	(kA)	50																																							
Características mecánicas																																									
Peso		1.34 kg																																							
TECNOLOGIA		MOV-GSG																																							
CONFIGURACION DE RED		3PH, 3W+G, Delta																																							
FORMA DE CONEXION		36" #12 AWG LEADS																																							
MONTAJE		SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)																																							
MATERIAL		Aluminum cast																																							
NEMA RATING (IP RATING)		6 (IP66)																																							
DESCONEXION SEGURA		Yes, no upstream over current protection required																																							
REAL-TIME DIAGNOSTICS		LED and audible alarm																																							
DIMENSIONS		See diagram																																							
WEIGHT		2.5 lbs.																																							
Normas																																									
UL STANDARD		UL1449 5th Edition																																							
UL CATEGORY		VZCA																																							
UL FILE NUMBER		E326289																																							
NORMAS		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																							
ENVIRONMENTAL STANDARDS		ROHS																																							
Código																																									
751404																																									