




CITEL



UL TYPE 1 SPD - I_{max} 50kA - I_n 20kA - AC Panel Mount

M50-240D-B

- ▶ Hybrid MOV-GSG Technology
- ▶ UL1449 Type 1 LISTED
- ▶ 50kA Surge Current Rating per mode
- ▶ Extended life with no leakage current
- ▶ Visual LED fault indicator and audible alarm
- ▶ NEMA 6 (exceeds NEMA 4X or 4)
- ▶ 10-Year warranty



| Características eléctricas | | |
|-------------------------------|------|---|
| POWER SPD TYPE | | UL1449 TYPE 1 LISTED |
| TENSION | (V) | 240 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3D |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -35 |
| AMBIENT MAX | (C) | +80 |
| MODOS | | L-L, L-G |
| VPR | (V) | 1200/-/1200/- |
| MCOV | (V) | 280/280/-/- |
| IN | (kA) | 20 |
| I _{cc cortocircuito} | (kA) | 150 |
| IMAX | (kA) | 50 |
| Características mecánicas | | |
| TECNOLOGIA | | MOV-GSG |
| CONFIGURACION DE RED | | 3PH, 3W+G, Delta |
| FORMA DE CONEXION | | 36" #12 AWG LEADS |
| MONTAJE | | BACK MOUNT, THREADED M22 (1/2" NPT ADAPTER) |
| MATERIAL | | Aluminum cast |
| NEMA RATING (IP RATING) | | 6 (IP66) |
| DESCONEXION SEGURA | | Yes, no upstream over current protection required |
| REAL-TIME DIAGNOSTICS | | LED and audible alarm |
| DIMENSIONS | | See diagram |
| WEIGHT | | 2.5 lbs. |
| Normas | | |
| Normas ambientales | | EU RoHS |
| UL STANDARD | | UL1449 5th Edition |
| UL CATEGORY | | VZCA, VZCA7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | NOM-003-SCFI-2014, NOM-001-SCFI-1993 |
| Código | | |
| 751414 | | |

