



- ↳ Hybrid MOV-GSG Technology
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator and audible alarm
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ 10-Year warranty

	Electrical Characteristics																																								
	<table border="1"> <tbody> <tr><td>POWER SPD TYPE</td><td></td><td>-</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>347/600</td></tr> <tr><td>AC/DC/DC PV/RF</td><td></td><td>AC</td></tr> <tr><td>PHASE</td><td>(PH)</td><td>3Y</td></tr> <tr><td>AMPS</td><td>(A)</td><td>N/A</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-35</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+80</td></tr> <tr><td>MODES</td><td></td><td>L-L, L-N, L-G, N-G</td></tr> <tr><td>VPR</td><td>(V)</td><td>3000/1500/1800/1800</td></tr> <tr><td>MCOV</td><td>(V)</td><td>690/400/400/350</td></tr> <tr><td>IN</td><td>(kA)</td><td>20</td></tr> <tr><td colspan="3"><i>15 impulses 8/20µs</i></td></tr> <tr><td>SCCR</td><td>(kA)</td><td>150</td></tr> </tbody> </table>	POWER SPD TYPE		-	VOLTS	(V)	347/600	AC/DC/DC PV/RF		AC	PHASE	(PH)	3Y	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODES		L-L, L-N, L-G, N-G	VPR	(V)	3000/1500/1800/1800	MCOV	(V)	690/400/400/350	IN	(kA)	20	<i>15 impulses 8/20µs</i>			SCCR	(kA)	150	
POWER SPD TYPE		-																																							
VOLTS	(V)	347/600																																							
AC/DC/DC PV/RF		AC																																							
PHASE	(PH)	3Y																																							
AMPS	(A)	N/A																																							
AMBIENT MIN	(C)	-35																																							
AMBIENT MAX	(C)	+80																																							
MODES		L-L, L-N, L-G, N-G																																							
VPR	(V)	3000/1500/1800/1800																																							
MCOV	(V)	690/400/400/350																																							
IN	(kA)	20																																							
<i>15 impulses 8/20µs</i>																																									
SCCR	(kA)	150																																							
Mechanical Characteristics																																									
	<table border="1"> <tbody> <tr><td>TECHNOLOGY</td><td>MOV-GSG</td></tr> <tr><td>NETWORK CONFIGURATION</td><td>3PH, 4W+G, Wye</td></tr> <tr><td>CONNECTION METHOD</td><td>36" #12 AWG LEADS</td></tr> <tr><td>MOUNTING</td><td>SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)</td></tr> <tr><td>MATERIAL</td><td>Aluminum cast</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td>6 (IP66)</td></tr> <tr><td>FAIL-SAFE BEHAVIOR</td><td>Yes, no upstream over current protection required</td></tr> <tr><td>REAL-TIME DIAGNOSTICS</td><td>LED and audible alarm</td></tr> <tr><td>DIMENSIONS</td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td>2.5 lbs.</td></tr> </tbody> </table>	TECHNOLOGY	MOV-GSG	NETWORK CONFIGURATION	3PH, 4W+G, Wye	CONNECTION METHOD	36" #12 AWG LEADS	MOUNTING	SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)	MATERIAL	Aluminum cast	NEMA RATING (IP RATING)	6 (IP66)	FAIL-SAFE BEHAVIOR	Yes, no upstream over current protection required	REAL-TIME DIAGNOSTICS	LED and audible alarm	DIMENSIONS	See diagram	WEIGHT	2.5 lbs.	Standards																			
TECHNOLOGY	MOV-GSG																																								
NETWORK CONFIGURATION	3PH, 4W+G, Wye																																								
CONNECTION METHOD	36" #12 AWG LEADS																																								
MOUNTING	SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)																																								
MATERIAL	Aluminum cast																																								
NEMA RATING (IP RATING)	6 (IP66)																																								
FAIL-SAFE BEHAVIOR	Yes, no upstream over current protection required																																								
REAL-TIME DIAGNOSTICS	LED and audible alarm																																								
DIMENSIONS	See diagram																																								
WEIGHT	2.5 lbs.																																								
	<table border="1"> <tbody> <tr><td>STANDARDS</td><td>NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td>ROHS</td></tr> </tbody> </table>	STANDARDS	NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS	Part number																																			
STANDARDS	NOM-003-SCFI-2014, NOM-001-SCFI-1993																																								
ENVIRONMENTAL STANDARDS	ROHS																																								
	751601																																								