





- ↳ Hybrid MOV-GSG Technology
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator and audible alarm
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ 10-Year warranty

	Características eléctricas	
	POWER SPD TYPE	-
	TENSION (V)	347/600
	AC/DC/DC PV/RF	AC
	FASE (PH)	3Y
	AMPS (A)	N/A
	AMBIENT MIN (C)	-35
	AMBIENT MAX (C)	+80
	MODOS	L-L, L-N, L-G, N-G
	VPR (V)	3000/1500/1800/1800
	MCOV (V)	690/400/400/350
	IN (kA)	20
	Icc cortocircuito (kA)	150
Características mecánicas		
	TECNOLOGIA	MOV-GSG
	CONFIGURACION DE RED	3PH, 4W+G, Wye
	FORMA DE CONEXION	36" #12 AWG LEADS
	MONTAJE	SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)
	MATERIAL	Aluminum cast
	NEMA RATING (IP RATING)	6 (IP66)
	DESCONEXION SEGURA	Yes, no upstream over current protection required
	REAL-TIME DIAGNOSTICS	LED and audible alarm
	DIMENSIONS	See diagram
	WEIGHT	2.5 lbs.
Normas		
	NORMAS	NOM-003-SCFI-2014, NOM-001-SCFI-1993
	ENVIRONMENTAL STANDARDS	ROHS
Código		
	751601	