



M50-600D-A



- Hybrid MOV-GSG Technology
- UL1449 Type 1 LISTED
- 50kA Surge Current Rating per mode
- Extended life with no leakage current
- Visual LED fault indicator and audible alarm
- NEMA 6 (exceeds NEMA 4X or 4)
- Optional Type 2 LISTED with UL1283 Filter
- 10-Year warranty

	Electrical Characteristics																																														
	<table border="1"> <tr><td>POWER SPD TYPE</td><td></td><td>UL1449 TYPE 1 LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>600</td></tr> <tr><td>AC/DC/DC PV/RF</td><td></td><td>AC</td></tr> <tr><td>PHASE</td><td>(PH)</td><td>3D</td></tr> <tr><td>AMPS</td><td>(A)</td><td>N/A</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-35</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+80</td></tr> <tr><td>MODES</td><td></td><td>L-L, L-G</td></tr> <tr><td>VPR</td><td>(V)</td><td>3000/-/1800/-</td></tr> <tr><td>MCOV</td><td>(V)</td><td>690/690/-/-</td></tr> <tr><td>IN</td><td>(kA)</td><td>20</td></tr> <tr><td>15 impulses 8/20μs</td><td></td><td></td></tr> <tr><td>SCCR</td><td>(kA)</td><td>200</td></tr> <tr><td>IMAX</td><td>(kA)</td><td>50</td></tr> <tr><td>8/20μs</td><td></td><td></td></tr> </table>	POWER SPD TYPE		UL1449 TYPE 1 LISTED	VOLTS	(V)	600	AC/DC/DC PV/RF		AC	PHASE	(PH)	3D	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODES		L-L, L-G	VPR	(V)	3000/-/1800/-	MCOV	(V)	690/690/-/-	IN	(kA)	20	15 impulses 8/20μs			SCCR	(kA)	200	IMAX	(kA)	50	8/20μs			
POWER SPD TYPE		UL1449 TYPE 1 LISTED																																													
VOLTS	(V)	600																																													
AC/DC/DC PV/RF		AC																																													
PHASE	(PH)	3D																																													
AMPS	(A)	N/A																																													
AMBIENT MIN	(C)	-35																																													
AMBIENT MAX	(C)	+80																																													
MODES		L-L, L-G																																													
VPR	(V)	3000/-/1800/-																																													
MCOV	(V)	690/690/-/-																																													
IN	(kA)	20																																													
15 impulses 8/20μs																																															
SCCR	(kA)	200																																													
IMAX	(kA)	50																																													
8/20μs																																															
	Mechanical Characteristics																																														
	<table border="1"> <tr><td>TECHNOLOGY</td><td></td><td>MOV-GSG</td></tr> <tr><td>NETWORK CONFIGURATION</td><td></td><td>3PH, 3W+G, Delta</td></tr> <tr><td>CONNECTION METHOD</td><td></td><td>36° #12 AWG LEADS</td></tr> <tr><td>MOUNTING</td><td></td><td>SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)</td></tr> <tr><td>MATERIAL</td><td></td><td>Aluminum cast</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>6 (IP66)</td></tr> <tr><td>FAIL-SAFE BEHAVIOR</td><td></td><td>Yes, no upstream over current protection required</td></tr> <tr><td>REAL-TIME DIAGNOSTICS</td><td></td><td>LED and audible alarm</td></tr> <tr><td>DIMENSIONS</td><td></td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td></td><td>2.5 lbs.</td></tr> </table>	TECHNOLOGY		MOV-GSG	NETWORK CONFIGURATION		3PH, 3W+G, Delta	CONNECTION METHOD		36° #12 AWG LEADS	MOUNTING		SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)	MATERIAL		Aluminum cast	NEMA RATING (IP RATING)		6 (IP66)	FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required	REAL-TIME DIAGNOSTICS		LED and audible alarm	DIMENSIONS		See diagram	WEIGHT		2.5 lbs.																
TECHNOLOGY		MOV-GSG																																													
NETWORK CONFIGURATION		3PH, 3W+G, Delta																																													
CONNECTION METHOD		36° #12 AWG LEADS																																													
MOUNTING		SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)																																													
MATERIAL		Aluminum cast																																													
NEMA RATING (IP RATING)		6 (IP66)																																													
FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required																																													
REAL-TIME DIAGNOSTICS		LED and audible alarm																																													
DIMENSIONS		See diagram																																													
WEIGHT		2.5 lbs.																																													
	Standards																																														
	<table border="1"> <tr><td>UL STANDARD</td><td></td><td>UL1449 5th Edition</td></tr> <tr><td>UL CATEGORY</td><td></td><td>VZCA</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E326289</td></tr> <tr><td>STANDARDS</td><td></td><td>NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td></td><td>ROHS</td></tr> </table>	UL STANDARD		UL1449 5th Edition	UL CATEGORY		VZCA	UL FILE NUMBER		E326289	STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																															
UL STANDARD		UL1449 5th Edition																																													
UL CATEGORY		VZCA																																													
UL FILE NUMBER		E326289																																													
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																													
ENVIRONMENTAL STANDARDS		ROHS																																													
	Part number																																														
	751804																																														