



M50-600D-A



- ↳ Hybrid MOV-GSG Technology
- ↳ UL1449 Type 1 LISTED
- ↳ 50kA Surge Current Rating per mode
- ↳ Extended life with no leakage current
- ↳ Visual LED fault indicator and audible alarm
- ↳ NEMA 6 (exceeds NEMA 4X or 4)
- ↳ Optional Type 2 LISTED with UL1283 Filter
- ↳ 10-Year warranty

	<b>Características eléctricas</b>																																								
	<table border="1"> <tr><td>POWER SPD TYPE</td><td></td><td>UL1449 TYPE 1 LISTED</td></tr> <tr><td>TENSION</td><td>(V)</td><td>600</td></tr> <tr><td>AC/DC/DC PV/RF</td><td></td><td>AC</td></tr> <tr><td>FASE</td><td>(PH)</td><td>3D</td></tr> <tr><td>AMPS</td><td>(A)</td><td>N/A</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-35</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+80</td></tr> <tr><td>MODOS</td><td></td><td>L-L, L-G</td></tr> <tr><td>VPR</td><td>(V)</td><td>3000/-/1800/-</td></tr> <tr><td>MCOV</td><td>(V)</td><td>690/690/-/-</td></tr> <tr><td>IN</td><td>(kA)</td><td>20</td></tr> <tr><td>I<sub>cc</sub> cortocircuito</td><td>(kA)</td><td>200</td></tr> <tr><td>IMAX</td><td>(kA)</td><td>50</td></tr> </table>	POWER SPD TYPE		UL1449 TYPE 1 LISTED	TENSION	(V)	600	AC/DC/DC PV/RF		AC	FASE	(PH)	3D	AMPS	(A)	N/A	AMBIENT MIN	(C)	-35	AMBIENT MAX	(C)	+80	MODOS		L-L, L-G	VPR	(V)	3000/-/1800/-	MCOV	(V)	690/690/-/-	IN	(kA)	20	I <sub>cc</sub> cortocircuito	(kA)	200	IMAX	(kA)	50	
POWER SPD TYPE		UL1449 TYPE 1 LISTED																																							
TENSION	(V)	600																																							
AC/DC/DC PV/RF		AC																																							
FASE	(PH)	3D																																							
AMPS	(A)	N/A																																							
AMBIENT MIN	(C)	-35																																							
AMBIENT MAX	(C)	+80																																							
MODOS		L-L, L-G																																							
VPR	(V)	3000/-/1800/-																																							
MCOV	(V)	690/690/-/-																																							
IN	(kA)	20																																							
I <sub>cc</sub> cortocircuito	(kA)	200																																							
IMAX	(kA)	50																																							
	<b>Características mecánicas</b>																																								
	<table border="1"> <tr><td>TECNOLOGIA</td><td></td><td>MOV-GSG</td></tr> <tr><td>CONFIGURACION DE RED</td><td></td><td>3PH, 3W+G, Delta</td></tr> <tr><td>FORMA DE CONEXION</td><td></td><td>36" #12 AWG LEADS</td></tr> <tr><td>MONTAJE</td><td></td><td>SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)</td></tr> <tr><td>MATERIAL</td><td></td><td>Aluminum cast</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>6 (IP66)</td></tr> <tr><td>DESCONEXION SEGURA</td><td></td><td>Yes, no upstream over current protection required</td></tr> <tr><td>REAL-TIME DIAGNOSTICS</td><td></td><td>LED and audible alarm</td></tr> <tr><td>DIMENSIONES</td><td></td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td></td><td>2.5 lbs.</td></tr> </table>	TECNOLOGIA		MOV-GSG	CONFIGURACION DE RED		3PH, 3W+G, Delta	FORMA DE CONEXION		36" #12 AWG LEADS	MONTAJE		SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)	MATERIAL		Aluminum cast	NEMA RATING (IP RATING)		6 (IP66)	DESCONEXION SEGURA		Yes, no upstream over current protection required	REAL-TIME DIAGNOSTICS		LED and audible alarm	DIMENSIONES		See diagram	WEIGHT		2.5 lbs.										
TECNOLOGIA		MOV-GSG																																							
CONFIGURACION DE RED		3PH, 3W+G, Delta																																							
FORMA DE CONEXION		36" #12 AWG LEADS																																							
MONTAJE		SIDE MOUNT, THREADED M22 (1/2" NPT ADAPTER)																																							
MATERIAL		Aluminum cast																																							
NEMA RATING (IP RATING)		6 (IP66)																																							
DESCONEXION SEGURA		Yes, no upstream over current protection required																																							
REAL-TIME DIAGNOSTICS		LED and audible alarm																																							
DIMENSIONES		See diagram																																							
WEIGHT		2.5 lbs.																																							
	<b>Normas</b>																																								
	<table border="1"> <tr><td>UL STANDARD</td><td></td><td>UL1449 5th Edition</td></tr> <tr><td>UL CATEGORY</td><td></td><td>VZCA</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E326289</td></tr> <tr><td>NORMAS</td><td></td><td>NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td></td><td>ROHS</td></tr> </table>	UL STANDARD		UL1449 5th Edition	UL CATEGORY		VZCA	UL FILE NUMBER		E326289	NORMAS		NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																									
UL STANDARD		UL1449 5th Edition																																							
UL CATEGORY		VZCA																																							
UL FILE NUMBER		E326289																																							
NORMAS		NOM-003-SCFI-2014, NOM-001-SCFI-1993																																							
ENVIRONMENTAL STANDARDS		ROHS																																							
	<b>Código</b>																																								
	751804																																								