



CITEL

- UL Type 1/2 SPD - I_{max} 300kA per phase - I_n 20kA - NEMA Enclosure

MDS600S-240D



- UL1449 5th edition
- All Mode Protection
- I_{total}-600kA 8/20us
- I_{max}/phase-300kA 8/20us
- UL 1449 Nominal Discharge Current (I_n) 20kA (All models)
- UL 1449 Short-circuit Current Rating (SCCR) 200kA (All models)
- UL96A Master Label Compliant
- Surge Rated Disconnect Switch
- Smart Diagnostics - % of protection present, audible, remote alarm, test/mute
- Surge Counter
- Serviceable Individual Replaceable Modules
- Optional Listing as UL Type 2 with UL1283 Filter
- NEMA 4/12 (Stainless Steel NEMA 4X optional)
- Standard 10-year warranty

Características eléctricas		
IMAX	(kA)	300
Opción		
Remote status dry contact electrical rating	V	125.0000
Remote status dry contact electrical rating	A	0.5000
RFI Filter		Yes
Instalación		
Wiring type		Screw
Stranded Wire cross section	mm ²	5.0000
Wire gauge	AWG	10.0000
Torque	Nm	4
Torque	in-lbs	35
Operating Temperature	°C	-40.0000
Operating Temperature	°C	85.0000
Operating Temperature	°F	-40.0000
Operating Temperature	°F	85.0000
Operating Relative Humidity	%RH	95
Operating Altitude	Ft	2000.0000
Operating Altitude	Ft	6500.0000
Housing/Enclosure material		Metal
Flammability rating		V0
Mounting		WALL MOUNT
IP Environmental rating		IP56
NEMA Environmental rating		NEMA 4
Installation Location		Indoor / outdoor
Spare part		Module
Accesorio		Soportes
Product Dimension	mm	360.6000
Product Dimension	mm	406.4000
Product Dimension	mm	159.8000
Product Dimension	In	14.2000
Product Dimension	In	16.0000
Product Dimension	In	6.2900
Miscelánea		
Individual Pack		Yes
Storage Temperature	°C	-40.0000
Storage Temperature	°C	85.0000
Storage Temperature	°F	-40.0000
Storage Temperature	°F	85.0000
Características mecánicas		
DIMENSIONS		14.2x6.3x16 (LxWxH-inches)
Código		
890635		

