



CITEL

- UL Type 1/2 SPD - I_{max} 300kA per phase - I_n 20kA - NEMA Enclosure

MDS600E-240Y



- ✦ UL1449 5th edition
- ✦ All Mode Protection
- ✦ I_{total}-600kA 8/20us
- ✦ I_{max}/phase-300kA 8/20us
- ✦ UL 1449 Nominal Discharge Current (I_n) 20kA (All models)
- ✦ UL 1449 Short-circuit Current Rating (SCCR) 200kA (All models)
- ✦ UL96A Master Label Compliant
- ✦ Surge Rated Disconnect Switch
- ✦ Smart Diagnostics - % of protection present, audible, remote alarm, test/mute
- ✦ Surge Counter
- ✦ Serviceable Individual Replaceable Modules
- ✦ Optional Listing as UL Type 2 with UL1283 Filter
- ✦ NEMA 4/12 (Stainless Steel NEMA 4X optional)
- ✦ Standard 10-year warranty

Características eléctricas		
POWER SPD TYPE		UL1449 TYPE 1 LISTED
TENSION	(V)	120/208/240
AC/DC/DC PV/RF		AC
FASE	(PH)	3Y
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+85
MODOS		L-L, L-N, L-G, N-G
VPR	(V)	2500/1800/1800/1200
MCOV	(V)	640/320/320/275
IN	(kA)	20
I _{cc} cortocircuito	(kA)	200
IMAX	(kA)	300
Características mecánicas		
TECNOLOGIA		Multi-TMOV
CONFIGURACION DE RED		3PH, 4W+G, Wye
FORMA DE CONEXION		Screw Terminal (4-10AWG)
MONTAJE		FLANGE MOUNT
MATERIAL		Steel
NEMA RATING (IP RATING)		IP65
DESCONEXION SEGURA		Yes, no upstream over current protection required
REAL-TIME DIAGNOSTICS		% of protection present LED, audible alarm and remote contacts. Optional surge counter.
DIMENSIONS		14.2x6.3x16 (LxWxH-inches)
WEIGHT		17 lbs
Normas		
UL STANDARD		UL1449 5th Edition, UL1283
UL CATEGORY		VZCA, VZCA7, FOKY, FOKY7
UL FILE NUMBER		E326289, E467909
ANSI/IEEE C62.41		Category C 20kV/10kA
ENVIRONMENTAL STANDARDS		ROHS
Código		
890642		

