




CITEL

- UL497B LISTED - I_{max} 20kA - I_n 5kA - Modular - Data Speed 10/100 /1000

DLA2-06DBC



- › Hybrid SAD-GDT Technology
- › UL497B LISTED
- › 20kA I_{max}
- › 5kA I_{imp}
- › 5kA I_n
- › Modular
- › 4W+SHIELD+G



Electrical Characteristics		
Network		MIC/T2, 10BaseTRS485
Nominal line voltage	Un	6 V
Max. DC operating voltage	Uc	8 Vdc
Max. frequency	f max.	20 MHz
Max. load current @25°C	IL	300 mA
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max}	20 kA
Nominal discharge current <i>C2 Category</i>	I _n	5 kA
Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-Y (Line/Line)</i>	Up	25 V
Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-C (Line/Earth)</i>	Up	650 V
Impulse current <i>2 x 10/350μs Test - D1 Category</i>	I _{imp}	5 kA
Impulse current <i>D1 (10/350μs), 2 applications, X-C (Line/Earth)</i>	I _{imp}	5 kA
Line resistance (± 10%)		4.7 Ohm
DATA SPD TYPE		UL497B LISTED
VOLTS	(V)	6
WIRES		4W+SHIELD+GROUND
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-50
AMBIENT MAX	(C)	+85
RESIDUAL VOLTAGE	(V)	20
MCOV	(V)	8/72/72
IMAX <i>8/20μs</i>	(kA)	20
I _{imp} <i>10/350μs</i>	(kA)	5
DATA SPEED	(Mbps)	10/100/1000
FREQUENCY	(MHz)	20
INSERTION LOSS (@ FREQ)	(db)	< 1
CAPACITANCE	(pF)	< 50
Mechanical Characteristics		
Technology		GDT+TVS diode
Connection to Network		By screw terminal: cross section 0.5-2.5mm ²
Format		Plug-in DIN box
Mounting		Symmetrical rail 35 mm (EN 60715)
Operating and storage temperature		-40/+85°C
Protection rating		IP20
Failsafe mode		Short-circuit
TECHNOLOGY		SAD-GDT
NETWORK CONFIGURATION		2 Channels (4W+G)
CONNECTION METHOD		Screw Terminal
MOUNTING		Din Rail



CITEL

- UL497B LISTED - I_{max} 20kA - I_n 5kA - Modular - Data Speed 10/100 /1000

DLA2-06DBC

MATERIAL	Thermoplastic UL94-V0
NEMA RATING (IP RATING)	NEMA 2 (IP20)
DIMENSIONS	See diagram
WEIGHT	0.30 lbs
SPARE PART	DLA2M-06DBC
Standards	
Certification	UL Listed
Environmental standards	EU RoHS
UL STANDARD	UL497B
UL CATEGORY	QVGQ
UL FILE NUMBER	E184939
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
Part number	
640131	

