




# CITEL

## TSP15M-P-24D3



- 1 Pair Protection
- Modes of Protection L-L,L-G
- Conduit Mounting-1/2 inch NPT
- Direct Transducer Mount
- Parallel or Series Connection Options
- BABA-Build America-Buy America Compliant



### Electrical Characteristics

VOLTS	(V)	24
MAXIMUM LINE VOLTAGE	(V)	32
WIRES		4W+GROUND
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-55
AMBIENT MAX	(C)	+85
PROTECTION LEVEL	(V)	38
IN 15 impulses 8/20µs	(kA)	10
IMAX 8/20µs	(kA)	15

### Installation

Operating Relative HumidityMax	%RH	Can be submerged
Operating AltitudeMax	Ft	6500.0000
Housing/Enclosure material		Stainless Steel
Mounting		Conduit-1/2" NPT
Installation Location		Indoor / outdoor
Product DimensionL	mm	114.3000
Product DimensionH	mm	26.0000
Product DimensionW	mm	27.9400
Product DimensionL	In	4.5000
Product DimensionH	In	1.0000
Product DimensionW	In	1.1000
Product Weight	lbs	0.8000

### Miscellaneous

Individual Pack		Yes
-----------------	--	-----

### Mechanical Characteristics

CONNECTION METHOD		Parallel- #16 AWG Copper Wires-Tinned
-------------------	--	---------------------------------------

### Part number

6336

