




CITEL



UL TYPE 1 SPD - I_{max} 40kA - I_n 20kA - Modular

DS44US-600D

- ▶ MOV Technology
- ▶ UL1449 Type 1
- ▶ 40kA Surge Current Rating
- ▶ Visual fault indicator and remote contacts
- ▶ 10-Year warranty



| Características eléctricas | | |
|----------------------------------|------|--|
| POWER SPD TYPE | | UL1449 TYPE 1 LISTED |
| TENSION | (V) | 600 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3D |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -35 |
| AMBIENT MAX | (C) | +60 |
| MODOS | | L-L, L-G |
| VPR | (V) | 2500/-/2500/- |
| MCOV | (V) | 840/-/840/- |
| IN | (kA) | 20 |
| I _{cc} cortocircuito | (kA) | 100 |
| IMAX | (kA) | 40 |
| I _{imp} | (kA) | 4 |
| Características mecánicas | | |
| Modo de fallo | | Desconexión de la red Baja Tensión |
| TECNOLOGIA | | MOV |
| CONFIGURACION DE RED | | 3PH, 3W+G, Delta |
| FORMA DE CONEXION | | SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG |
| MONTAJE | | Din Rail |
| MATERIAL | | Thermoplastic UL94-V0 |
| NEMA RATING (IP RATING) | | NEMA 2 (IP20) |
| DESCONEXION SEGURA | | Disconnection via fuse-link |
| REAL-TIME DIAGNOSTICS | | Visual indicator and remote contacts |
| DIMENSIONS | | See diagram |
| WEIGHT | | 1.20 lbs |
| SPARE PART | | DSM40-600 |
| Normas | | |
| Certificación | | CSA / UL Listed |
| UL STANDARD | | UL1449 5th Edition |
| UL CATEGORY | | VZCA, VZCA7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | NOM-003-SCFI-2014, NOM-001-SCFI-1993 |
| ENVIRONMENTAL STANDARDS | | ROHS |
| Código | | |
| 33141455 | | |

