



CITEL

UL TYPE 1/2 LISTED SPD - I_{max} 105kA per phase - In 20kA - NEMA 3R /4/12

MS80-240Y



- Multi-TMOV Technology
- UL1449 Type 1 LISTED
- BABA-Build America-Buy America compliant
- 105-220kA Surge Current Rating
- Visual fault indicator, audible alarm and remote contacts
- 10-Year warranty

| Características eléctricas | | |
|---|------------------|---|
| Corriente de descarga máxima <i>Capacidad máx. En onda 8/20µs por polo</i> | I _{max} | 105 kA |
| POWER SPD TYPE | | UL1449 TYPE 1 LISTED |
| TENSION | (V) | 240/415 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3Y |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -40 |
| AMBIENT MAX | (C) | +85 |
| MODOS | | L-L, L-N, L-G, N-G |
| VPR | (V) | 1800/1000/1200/1000 |
| MCOV | (V) | 640/320/320/320 |
| IN | (kA) | 20 |
| IMAX | (kA) | 105 |
| Características mecánicas | | |
| Conexión a la red | | hijo #10 AWG 36" |
| Montaje | | Montaje en pared mediante tornillos (no suministrado) |
| Temperatura de operación | Tu | -40/+85°C |
| TECNOLOGIA | | Multi-TMOV |
| CONFIGURACION DE RED | | 3PH, 4W+G, Wye |
| FORMA DE CONEXION | | 36" #10 AWG LEADS |
| MONTAJE | | FLANGE MOUNT |
| MATERIAL | | Steel |
| NEMA RATING (IP RATING) | | NEMA 3R,4, 12 (IP65) |
| DESCONEXION SEGURA | | Yes, no upstream over current protection required |
| REAL-TIME DIAGNOSTICS | | % of protection present LED, audible alarm and remote contacts. Optional surge counter. |
| DIMENSIONS | | See diagram |
| WEIGHT | | 6 lbs |
| Normas | | |
| Normas ambientales | | EU RoHS |
| UL STANDARD | | UL1449 5th Edition, UL1283 |
| UL CATEGORY | | VZCA, VZCA7, FOKY, FOKY7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | UL96A, ANSI C62.41/45, NOM-003-SCFI-2014, NOM-001-SCFI-1993, IEC61643-11 |
| BABA | | Build America-Buy America Compliant |
| Código | | |
| 890156 | | |

