



- Low Frequency Coaxial Surge Protector • High Energy GDT Technology • Bi-Directional Protection • IP20 or IP65 Classification • RoHS 6 Compliant • Waterproof Design • Bi-directional

Electrical Characteristics		
Network		Coaxial 125-1000 MHz
Max. DC operating voltage	Uc	< 60 Vdc
Max. frequency	f max.	125-1000 MHz
Insertion loss		< 1 dB
Return loss		> 20 dB
Impedance		50 ohms
VSWR		<1.2:1
Max. load current @25°C	IL	0.5 A
Protection mode(s)		Common mode
Impulse current <i>2 x 10/350µs Test - D1 Category</i>	limp	2.5 kA
Nominal discharge current <i>C2 Category</i>	In	5 kA
Max Power		25 W
DC Pass		No
Insulation resistance	IR	≥10 GOhms
RF Power <i>Maximum</i>	W	25.0000
Return Loss <i>Minimum</i>	db	>20
VSWR <i>Maximum</i>	:1	<1.3:1
Max Discharge Current <i>Imax (8/20µs x 1)</i>	kA	20.0000
Max Total Discharge Current <i>Imax (8/20µs x 1)</i>	kA	20.0000
Max Discharge Current <i>Imax (8/20µs x 1)</i>	kA	20.0000
Max Discharge Current <i>Imax (8/20µs x 1)</i>	kA	20.0000
Max Discharge Current <i>Imax (8/20µs x 1)</i>	kA	20.0000
Max Discharge Current <i>Imax (8/20µs x 1)</i>	kA	20.0000
Let through Voltage <i>at In</i>	V	600.0000
Installation		
Operating Temperature <i>Min</i>	°C	-40.0000
Operating Temperature <i>Max</i>	°C	85.0000
Operating Temperature <i>Min</i>	°F	-40.0000
Operating Temperature <i>Max</i>	°F	85.0000
Operating Relative Humidity <i>Max</i>	%RH	95
Operating Altitude <i>Min</i>	Ft	2000.0000
Operating Altitude <i>Max</i>	Ft	6500.0000
Housing/Enclosure material		BRASS
Mounting		Surface mount
IP Environmental rating/IP		IP20
Installation Location		Indoor / outdoor
Accessories		90° Stainless steel bracket
Product Dimension <i>L</i>	mm	93.9000
Product Dimension <i>W</i>	mm	30.8000
Product Dimension <i>L</i>	In	3.6900
Product Dimension <i>W</i>	In	1.2100
Miscellaneous		
Individual Pack		No
Storage Temperature <i>Min</i>	°C	-40.0000
Storage Temperature <i>Max</i>	°C	85.0000
Storage Temperature <i>Min</i>	°F	-40.0000
Storage Temperature <i>Max</i>	°F	85.0000
Storage Relative Humidity <i>Max</i>	%RH	95.0000
Installation		
Cable type		Coax
Mechanical Characteristics		

Technology	GDT+Filter
DC Block	Yes
Connection to Network	Connector N Male/Female
Format	Metallic box
Failsafe mode	Short-circuit
Part number	
6316531	