




- ↳ 1 Pair Protection
- ↳ Modes of Protection L-L,L-G
- ↳ Conduit Mounting-1/2 inch NPT
- ↳ Direct Transducer Mount
- ↳ Parallel or Series Connection Options



Características eléctricas		
TENSION	(V)	24
MAXIMUM LINE VOLTAGE	(V)	32
WIRES		4W+GROUND
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-55
AMBIENT MAX	(C)	+85
PROTECTION LEVEL	(V)	38
IN	(kA)	10
IMAX	(kA)	15
Instalación		
Operating Relative Humidity	%RH	Can be submerged
Operating Altitude	Ft	2000.0000
Operating Altitude	Ft	6500.0000
Housing/Enclosure material		Stainless Steel
Mounting		Conduit-1/2" NPT
Installation Location		Indoor / outdoor
Product Dimension	mm	114.3000
Product Dimension	mm	26.0000
Product Dimension	mm	27.9400
Product Dimension	In	4.5000
Product Dimension	In	1.0000
Product Dimension	In	1.1000
Product Weight	g	363.0000
Product Weight	lbs	0.8000
Miscelánea		
Individual Pack		Yes
Características mecánicas		
FORMA DE CONEXION		Series- #16 AWG Copper Wires-Tinned
Código		
6337		