



# CITEL



## M160-220Y

- Type 2 AC Power Surge Protector
- I<sub>max</sub>: 80-200kA per phase
- Protects All Modes
- On Board Diagnostics: LED indicators, Audible Alarm and Remote Contacts
- EMI/RFI Noise Filtering
- Sinewave Tracking
- UL 1449 4th Edition Listed
- Optional Surge Counter

Características eléctricas		
POWER SPD TYPE		UL1449 TYPE 2 LISTED
TENSION	(V)	380/220
AC/DC/DC PV/RF		AC
FASE	(PH)	3Y
AMPS	(A)	N/A
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	85
MODOS		L-L, L-N, L-G, N-G
VPR	(V)	2000/1200/1200/1200
MCOV	(V)	640/320/320/320
IN	(kA)	5
I <sub>cc</sub> <i>cortocircuito</i>	(kA)	200
IMAX	(kA)	200
I <sub>imp</sub>	(kA)	6
Características mecánicas		
TECNOLOGIA		Multi-MOV+EMI/RFI Filter
CONFIGURACION DE RED		3PH, 4W+G, Wye
FORMA DE CONEXION		36" #10 AWG LEADS
MONTAJE		FLANGE MOUNT
MATERIAL		Steel
NEMA RATING (IP RATING)		4/12
DESCONEXION SEGURA		30A upstream overcurrent device
REAL-TIME DIAGNOSTICS		LED, audible alarm and remote contacts.
DIMENSIONS		See diagram
WEIGHT		6 lbs
Normas		
Normas ambientales		EU RoHS
UL STANDARD		UL1449 5th Edition
UL CATEGORY		VZCA, VZCA7
UL FILE NUMBER		E326289
NORMAS		NOM-003-SCFI-2014
Código		
<b>89073877</b>		

