




CITEL



MP80-277Y

- ▶ Multi-TMOV Technology
- ▶ UL1449 Type 1 LISTED
- ▶ 88kA Surge Current Rating
- ▶ Visual fault indicator (LED per phase)
- ▶ 10-Year warranty



Características eléctricas

| | | |
|----------------|------|----------------------|
| POWER SPD TYPE | | UL1449 TYPE 1 LISTED |
| TENSION | (V) | 277/480 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3Y |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -40 |
| AMBIENT MAX | (C) | 85 |
| MODOS | | L-L, L-N, L-G, N-G |
| VPR | (V) | 1800/1000/1200/1000 |
| MCOV | (V) | 640/320/320/320 |
| IN | (kA) | 20 |
| IMAX | (kA) | 88 |

Características mecánicas

| | | |
|-------------------------|--|---|
| TECNOLOGIA | | Multi-TMOV |
| CONFIGURACION DE RED | | 3PH, 4W+G, Wye |
| FORMA DE CONEXION | | 36" #10 AWG LEADS |
| MONTAJE | | FLANGE MOUNT |
| MATERIAL | | Polycarbonate |
| NEMA RATING (IP RATING) | | 4X (IP67) |
| DESCONEXION SEGURA | | Yes, no upstream over current protection required |
| REAL-TIME DIAGNOSTICS | | LED Visual Status Indicators |
| DIMENSIONS | | See diagram |
| WEIGHT | | 6 lbs |

Normas

| | | |
|--------------------|--|--------------------|
| Normas ambientales | | EU RoHS |
| UL STANDARD | | UL1449 5th Edition |
| UL CATEGORY | | VZCA, VZCA7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | NOM-003-SCFI-2014 |

Código

891859

