



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x-8/20us)
- ↳ 5kA I_{imp} (2x-10/350us)
- ↳ 5kA I_n (10x-8/20us)
- ↳ Modular
- ↳ 2W+SHIELD+G



	Características eléctricas																																																	
<p>G : Descargador tripolar Gb : Descargador bipolar R : Resistor D : Diodo limitador</p>	<table border="1"> <tr><td>Resistencia en línea (± 10%)</td><td></td><td>4.7 Ohm</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL Listed for Hazardous Locations</td></tr> <tr><td>TENSION</td><td>(V)</td><td>6</td></tr> <tr><td>WIRES</td><td></td><td>2W+Shield+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>20</td></tr> <tr><td>MCOV</td><td>(V)</td><td>8</td></tr> <tr><td>IN</td><td>(kA)</td><td>5</td></tr> <tr><td>IMAX</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp}</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>FREQUENCY</td><td>(MHz)</td><td>up to 10</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> <tr><td>CAPACITANCE</td><td>(pF)</td><td>< 50</td></tr> </table>		Resistencia en línea (± 10%)		4.7 Ohm	DATA SPD TYPE		UL Listed for Hazardous Locations	TENSION	(V)	6	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	20	MCOV	(V)	8	IN	(kA)	5	IMAX	(kA)	20	I _{imp}	(kA)	5	DATA SPEED	(Mbps)	10/100	FREQUENCY	(MHz)	up to 10	INSERTION LOSS (@ FREQ)	(db)	< 1	CAPACITANCE	(pF)	< 50
Resistencia en línea (± 10%)		4.7 Ohm																																																
DATA SPD TYPE		UL Listed for Hazardous Locations																																																
TENSION	(V)	6																																																
WIRES		2W+Shield+G																																																
LINE CURRENT MAX	(A)	0.3																																																
AMBIENT MIN	(C)	-40																																																
AMBIENT MAX	(C)	+85																																																
RESIDUAL VOLTAGE	(V)	20																																																
MCOV	(V)	8																																																
IN	(kA)	5																																																
IMAX	(kA)	20																																																
I _{imp}	(kA)	5																																																
DATA SPEED	(Mbps)	10/100																																																
FREQUENCY	(MHz)	up to 10																																																
INSERTION LOSS (@ FREQ)	(db)	< 1																																																
CAPACITANCE	(pF)	< 50																																																
Características mecánicas																																																		
<table border="1"> <tr><td>Modo de fallo</td><td>Corto-circuito</td></tr> <tr><td>TECNOLOGIA</td><td>SAD-GDT</td></tr> <tr><td>CONFIGURACION DE RED</td><td>1 Channel (2W+SHIELD+G)</td></tr> <tr><td>FORMA DE CONEXION</td><td>Screw terminal</td></tr> <tr><td>MONTAJE</td><td>Din rail</td></tr> <tr><td>MATERIAL</td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td>DLAM-06D3</td></tr> </table>		Modo de fallo	Corto-circuito	TECNOLOGIA	SAD-GDT	CONFIGURACION DE RED	1 Channel (2W+SHIELD+G)	FORMA DE CONEXION	Screw terminal	MONTAJE	Din rail	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	DLAM-06D3																													
Modo de fallo	Corto-circuito																																																	
TECNOLOGIA	SAD-GDT																																																	
CONFIGURACION DE RED	1 Channel (2W+SHIELD+G)																																																	
FORMA DE CONEXION	Screw terminal																																																	
MONTAJE	Din rail																																																	
MATERIAL	Thermoplastic UL94-V0																																																	
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																																	
DIMENSIONS	See diagram																																																	
WEIGHT	0.30 lbs																																																	
SPARE PART	DLAM-06D3																																																	
Normas																																																		
<table border="1"> <tr><td>Certificación</td><td>UL Listed</td></tr> <tr><td>UL STANDARD</td><td>UL497B & UL121201 Hazardous Location</td></tr> <tr><td>UL CATEGORY</td><td>QVQ & QVSI</td></tr> <tr><td>UL FILE NUMBER</td><td>E184939 & E527349</td></tr> <tr><td>UL121201 HAZARDOUS LOCATION</td><td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td></tr> <tr><td>NORMAS</td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td>ROHS</td></tr> </table>		Certificación	UL Listed	UL STANDARD	UL497B & UL121201 Hazardous Location	UL CATEGORY	QVQ & QVSI	UL FILE NUMBER	E184939 & E527349	UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	NORMAS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS																																			
Certificación	UL Listed																																																	
UL STANDARD	UL497B & UL121201 Hazardous Location																																																	
UL CATEGORY	QVQ & QVSI																																																	
UL FILE NUMBER	E184939 & E527349																																																	
UL121201 HAZARDOUS LOCATION	Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																																	
NORMAS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																	
ENVIRONMENTAL STANDARDS	ROHS																																																	
Código																																																		
897011																																																		

