



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x-8/20us)
- ↳ 5kA I_{imp} (2x-10/350us)
- ↳ 5kA I_n (10x-8/20us)
- ↳ Modular
- ↳ 2W+SHIELD+G



	Características eléctricas																																					
<p>G : Descargador tripolar Gb : Descargador bipolar R : Resistor D : Diodo limitador</p>	<table border="1"> <tr><td>Resistencia en línea (± 10%)</td><td></td><td>4.7 Ohm</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL Listed for Hazardous Locations</td></tr> <tr><td>TENSION</td><td>(V)</td><td>24</td></tr> <tr><td>WIRES</td><td></td><td>2W+Shield+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>0.3</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-40</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>40</td></tr> <tr><td>MCOV</td><td>(V)</td><td>28</td></tr> <tr><td>IN</td><td>(kA)</td><td>5</td></tr> <tr><td>IMAX</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp}</td><td>(kA)</td><td>5</td></tr> </table>		Resistencia en línea (± 10%)		4.7 Ohm	DATA SPD TYPE		UL Listed for Hazardous Locations	TENSION	(V)	24	WIRES		2W+Shield+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-40	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	40	MCOV	(V)	28	IN	(kA)	5	IMAX	(kA)	20	I _{imp}	(kA)	5
Resistencia en línea (± 10%)		4.7 Ohm																																				
DATA SPD TYPE		UL Listed for Hazardous Locations																																				
TENSION	(V)	24																																				
WIRES		2W+Shield+G																																				
LINE CURRENT MAX	(A)	0.3																																				
AMBIENT MIN	(C)	-40																																				
AMBIENT MAX	(C)	+85																																				
RESIDUAL VOLTAGE	(V)	40																																				
MCOV	(V)	28																																				
IN	(kA)	5																																				
IMAX	(kA)	20																																				
I _{imp}	(kA)	5																																				
Características mecánicas																																						
<table border="1"> <tr><td>Modo de fallo</td><td></td><td>Corto-circuito</td></tr> <tr><td>TECNOLOGIA</td><td></td><td>SAD-GDT</td></tr> <tr><td>CONFIGURACION DE RED</td><td></td><td>1 Channel (2W+SHIELD+G)</td></tr> <tr><td>FORMA DE CONEXION</td><td></td><td>Screw terminal</td></tr> <tr><td>MONTAJE</td><td></td><td>Din rail</td></tr> <tr><td>MATERIAL</td><td></td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td></td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td></td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td></td><td>DLAM-24D3</td></tr> </table>			Modo de fallo		Corto-circuito	TECNOLOGIA		SAD-GDT	CONFIGURACION DE RED		1 Channel (2W+SHIELD+G)	FORMA DE CONEXION		Screw terminal	MONTAJE		Din rail	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLAM-24D3						
Modo de fallo		Corto-circuito																																				
TECNOLOGIA		SAD-GDT																																				
CONFIGURACION DE RED		1 Channel (2W+SHIELD+G)																																				
FORMA DE CONEXION		Screw terminal																																				
MONTAJE		Din rail																																				
MATERIAL		Thermoplastic UL94-V0																																				
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																				
DIMENSIONS		See diagram																																				
WEIGHT		0.30 lbs																																				
SPARE PART		DLAM-24D3																																				
Normas																																						
<table border="1"> <tr><td>Certificación</td><td></td><td>UL Listed</td></tr> <tr><td>UL STANDARD</td><td></td><td>UL497B & UL121201 Hazardous Location</td></tr> <tr><td>UL CATEGORY</td><td></td><td>QVGQ & QVSI</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E184939 & E527349</td></tr> <tr><td>UL121201 HAZARDOUS LOCATION</td><td></td><td>Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5</td></tr> <tr><td>NORMAS</td><td></td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td></td><td>ROHS</td></tr> </table>			Certificación		UL Listed	UL STANDARD		UL497B & UL121201 Hazardous Location	UL CATEGORY		QVGQ & QVSI	UL FILE NUMBER		E184939 & E527349	UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5	NORMAS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS															
Certificación		UL Listed																																				
UL STANDARD		UL497B & UL121201 Hazardous Location																																				
UL CATEGORY		QVGQ & QVSI																																				
UL FILE NUMBER		E184939 & E527349																																				
UL121201 HAZARDOUS LOCATION		Class I, Division 2, Groups A, B, C & D: Operating. Temp. T5																																				
NORMAS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																				
ENVIRONMENTAL STANDARDS		ROHS																																				
Código																																						
897014																																						

