



CITEL

100kA Rated SPD - Integrated Surge Tolerant Disconnect Switch

iMDS100-208D



- Multi-MOV Technology
- 100kA Max Surge Current Rating per Phase
- Visual and Audible Protection Status Indicators
- Remote Contacts
- Modular/Serviceable Design
- Surge Tolerant External Disconnect Switch
- 10-Year warranty

Electrical Characteristics		
VOLTS	(V)	240
AC/DC/DC PV/RF		AC
PHASE	(PH)	3D
AMPS	(A)	N/A
AMBIENT MIN	(C)	-40
AMBIENT MAX	(C)	+85
MODES		L-L, L-G
VPR	(V)	1000/-/1000/-
MCOV	(V)	300/-/300/-
IN 15 impulses 8/20µs	(kA)	20
SCCR	(kA)	200
IMAX 8/20µs	(kA)	100
RELATIVE HUMIDITY	(%)	95%
Mechanical Characteristics		
TECHNOLOGY		Multi-MOV
NETWORK CONFIGURATION		3PH, 3W+G, Delta
CONNECTION METHOD		Screw Terminal (4-14AWG)
DISCONNECTION		External Surge Tolerant Switch
MOUNTING		FLANGE MOUNT
MATERIAL		Steel
NEMA RATING (IP RATING)		NEMA 4
FAIL-SAFE BEHAVIOR		Yes, no upstream over current protection required
REAL-TIME DIAGNOSTICS		% of protection present LED, audible alarm, and remote contacts
DIMENSIONS		See diagram
Standards		
UL STANDARD		UL508A
UL CATEGORY		NITW
UL FILE NUMBER		E532119
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Part number		
890676		

