



CITEL

Outdoor DC Power Surge Protective Device

CPDIN40S-75DC-1P



- IP67 Outdoor Rated Enclosure
- I_{max} 40kA
- Replaceable DIN Rail Module
- Remote Contacts
- Surface Mount/Flange Mount
- Pole Mount Bracket Kit



Electrical Characteristics		
Max. DC operating voltage	Uc	65 Vdc
VOLTS	(V)	75
AC/DC/DC PV/RF		DC
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+85
MODES		DC+G or DC-G
MLV DC	(V)	1369
MCOV	(V)	100
IN	(kA)	20
15 impulses 8/20µs		
IMAX	(kA)	40
8/20µs		
Mechanical Characteristics		
Technology		MOV
APPLICATION		Outdoor 75V DC Power
TECHNOLOGY		MOV
NETWORK CONFIGURATION		2W+G
CONNECTION METHOD		SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MOUNTING		FLANGE MOUNT/POLE MOUNT KIT
MATERIAL		Polycarbonate
NEMA RATING (IP RATING)		NEMA 6P (IP67)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Remote contacts
DIMENSIONS		See diagram
WEIGHT		2.5 lbs.
Standards		
ENVIRONMENTAL STANDARDS		ROHS
Part number		
893019		

