



CITEL



CPDIN20S-12DC-1

- › IP67 Outdoor Rated Enclosure
- › I_{max} 20kA
- › Replaceable DIN Rail Module
- › Surface Mount/Flange Mount
- › Remote Contacts



Electrical Characteristics		
VOLTS	(V)	12
AC/DC/DC PV/RF		DC
AMBIENT MIN	(C)	-40
AMBIENT MAX	(C)	+85
MODES		DC+G or DC-G
MLV DC	(V)	510
MCOV	(V)	24
IN	(kA)	10
<i>15 impulses 8/20μs</i>		
IMAX	(kA)	20
<i>8/20μs</i>		
Mechanical Characteristics		
Technology		MOV
APPLICATION		Outdoor 12V DC Power
TECHNOLOGY		MOV
NETWORK CONFIGURATION		2W+G
CONNECTION METHOD		SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MOUNTING		FLANGE MOUNT
MATERIAL		Polycarbonate
NEMA RATING (IP RATING)		NEMA 6P (IP67)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Remote contacts
DIMENSIONS		See diagram
WEIGHT		2.5 lbs.
Standards		
Environmental standards		EU RoHS
Part number		
893011		

