





- ✦ MOV Technology
- ✦ UL1449 5th Edition - Type 1
- ✦ 40kA Surge Current Rating
- ✦ Visual fault indicator and remote contacts
- ✦ 10-Year warranty



V: High-energy varistor  
 Ft: Thermal fuse  
 t\*: Thermal disconnection system  
 MI: Disconnection indicator C: Remote signal contact

Electrical Characteristics	
Network	PV 1250 Vdc
Protection mode(s)	Common/Differential mode
POWER SPD TYPE	UL1449 TYPE 1 LISTED
VOLTS	(V) 1500
AC/DC/DC PV/RF	DC PV
PHASE	(PH) -
AMPS	(A) N/A
AMBIENT MIN	(C) -40
AMBIENT MAX	(C) +85
MODES	DC+DC-, DC+G, DC-G
VPR	(V) 4000/4000/4000
MCOV	(V) 1500/1500/1500
IN	(kA) 10
15 impulses 8/20µs	
SCCR	(kA) 100
IMAX	(kA) 40
8/20µs	
Mechanical Characteristics	
Technology	MOV
Connection to Network	By screw terminals: 2.5-25mm <sup>2</sup> / by bus
Format	Plug-in modular box
Failsafe mode	Disconnection SPD of the PV line
Weight	0.334 kg
TECHNOLOGY	
NETWORK CONFIGURATION	3 poles, 2W+G
CONNECTION METHOD	SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MOUNTING	DIN RAIL
MATERIAL	Thermoplastic UL94-V0
NEMA RATING (IP RATING)	NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR	Disconnection via fuse-link
REAL-TIME DIAGNOSTICS	Visual indicator and remote contacts
DIMENSIONS	See diagram
Standards	
Certification	UL Listed
UL STANDARD	UL1449 5th Edition
UL FILE NUMBER	E326289
Part number	
48057155	

