




CITEL

UL TYPE 2 LISTED SPD - I_{max} 105kA per phase - I_n 20kA - NEMA 3R/4 /12

MS80F-347Y



- Multi-TMOV Technology
- UL1449 Type 2 LISTED
- UL1283 LISTED EMI/RFI Filter
- BABA-Build America-Buy America compliant
- 105kA Surge Current Rating
- Connection Type-Parallel
- Operating Frequency-47Hz-63Hz
- Response time- <50 ns
- Visual fault indicator
- 10-Year warranty



| Características eléctricas | | |
|----------------------------|------|--|
| POWER SPD TYPE | | UL1449 TYPE 2 LISTED |
| TENSION | (V) | 347/600 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3Y |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -40 |
| AMBIENT MAX | (C) | +85 |
| MODOS | | L-L, L-N, L-G, N-G |
| VPR | (V) | 3000/1800/1800/1800 |
| MCOV | (V) | 1100/550/550/550 |
| IN | (kA) | 20 |
| I _{cc} | (kA) | 200 |
| <i>cortocircuito</i> | | |
| IMAX | (kA) | 105 |
| Características mecánicas | | |
| TECNOLOGIA | | Multi-TMOV |
| CONFIGURACION DE RED | | 3PH, 4W+G, Wye |
| FORMA DE CONEXION | | 36" #10 AWG LEADS |
| MONTAJE | | FLANGE MOUNT |
| MATERIAL | | Steel |
| NEMA RATING (IP RATING) | | IP65 |
| DESCONEXION SEGURA | | Disconnection via fuse-link |
| REAL-TIME DIAGNOSTICS | | % of protection present LED, audible alarm and remote contacts. |
| DIMENSIONS | | See diagram |
| WEIGHT | | 6 lbs |
| Normas | | |
| Certificación | | UL Listed |
| Normas ambientales | | EU RoHS |
| UL STANDARD | | UL1449 5th Edition, UL1283 |
| UL CATEGORY | | VZCA, VZCA7, FOKY, FOKY7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | UL96A, ANSI C62.41/45, NOM-003-SCFI-2014, NOM-001-SCFI-1993, IEC61643-11 |
| BABA | | Build America-Buy America Compliant |
| Código | | |
| 890159 | | |

