




CITEL

UL TYPE 2 LISTED SPD - I_{max} 220kA per phase - I_n 20kA - NEMA 3R/4 /12

MS200F-277Y-C



- Multi-TMOV Technology
- UL1449 Type 1 LISTED
- BABA-Build America-Buy America compliant
- 220kA Surge Current Rating
- Visual fault indicator, audible alarm and remote contacts
- 10-Year warranty



| Características eléctricas | | |
|----------------------------|------|--|
| POWER SPD TYPE | | UL1449 TYPE 2 LISTED |
| TENSION | (V) | 277/480 |
| AC/DC/DC PV/RF | | AC |
| FASE | (PH) | 3Y |
| AMPS | (A) | N/A |
| AMBIENT MIN | (C) | -40 |
| AMBIENT MAX | (C) | 85 |
| MODOS | | L-L, L-N, L-G, N-G |
| VPR | (V) | 1800/1000/1200/1000 |
| MCOV | (V) | 640/320/320/320 |
| IN | (kA) | 20 |
| I _{cc} | (kA) | 150 |
| <i>cortocircuito</i> | | |
| IMAX | (kA) | 220 |
| Características mecánicas | | |
| TECNOLOGIA | | Multi-TMOV |
| CONFIGURACION DE RED | | 3PH, 4W+G, Wye |
| FORMA DE CONEXION | | 36" #10 AWG LEADS |
| MONTAJE | | FLANGE MOUNT |
| MATERIAL | | Steel |
| NEMA RATING (IP RATING) | | NEMA 3R,4, 12 (IP65) |
| DESCONEXION SEGURA | | Disconnection via fuse-link |
| REAL-TIME DIAGNOSTICS | | % of protection present LED, audible alarm, remote contacts and surge counter. |
| DIMENSIONS | | See diagram |
| WEIGHT | | 6 lbs |
| Normas | | |
| Certificación | | UL Listed |
| Normas ambientales | | EU RoHS |
| UL STANDARD | | UL1449 5th Edition |
| UL CATEGORY | | VZCA, VZCA7, FOKY, FOKY7 |
| UL FILE NUMBER | | E326289 |
| NORMAS | | NOM-003-SCFI-2014 |
| BABA | | Build America-Buy America Compliant |
| Código | | |
| 890225 | | |

