



CITEL

UL497B LISTED - I_{max} 20kA - I_n 5kA - Modular

DLA-12D3G



- Hybrid SAD-GDT Technology
- Compact 6mm module
- UL497B LISTED
- 10kA I_{max} (1x 8/20 μ s)
- 2.5kA I_{imp} (2x 10/350 μ s)
- 5kA I_n (10x 8/20 μ s)
- 2W+SHIELD+G
- Common/Differential mode protection

	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Network</td> <td>0-10 V analogic line, 12 V digital</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un 12 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc 15 Vdc</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL 750 mA</td> </tr> <tr> <td>Max. discharge current <i>max. withstand @ 8/20 μs by pole</i></td> <td>I_{max} 20 kA</td> </tr> <tr> <td>Nominal Discharge Current <i>C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)</i></td> <td>I_n 10 kA</td> </tr> <tr> <td>Nominal Discharge Current <i>C2 (1.2/50μs / 8/20μs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)</i></td> <td>I_n 10 kA</td> </tr> <tr> <td>Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)</i></td> <td>Up 40 V</td> </tr> <tr> <td>Protection Level <i>C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</i></td> <td>Up 650 V</td> </tr> <tr> <td>Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)</i></td> <td>Up 650 V</td> </tr> <tr> <td>Impulse current <i>D1 (10/350μs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C</i></td> <td>I_{imp} 2.5 kA</td> </tr> <tr> <td>Line resistance ($\pm 10\%$)</td> <td>1.5 Ohm</td> </tr> <tr> <td>DATA SPD TYPE</td> <td>UL497B LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V) 6</td> </tr> <tr> <td>WIRES</td> <td>2W+Shield+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A) 0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C) -50</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C) +85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V) 20</td> </tr> <tr> <td>MCOV</td> <td>(V) 8/72/72</td> </tr> <tr> <td>IN <i>10 impulses 8/20μs</i></td> <td>(kA) 5</td> </tr> <tr> <td>IMAX <i>8/20μs</i></td> <td>(kA) 10</td> </tr> <tr> <td>I_{imp} <i>10/350μs</i></td> <td>(kA) 2.5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps) up to 10MHz</td> </tr> <tr> <td>FREQUENCY</td> <td>(MHz) up to 10</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db) < 1</td> </tr> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> <tr> <td>Technology</td> <td>GDT+TVS diode</td> </tr> <tr> <td>Connection to Network</td> <td>By spring terminal - max. cross section 2.5mm² / AWG 13 (solid or stranded)</td> </tr> <tr> <td>Format</td> <td>DIN box</td> </tr> <tr> <td>Operating temperature</td> <td>Tu -40/+85°C</td> </tr> <tr> <td>Ingress Protection rating</td> <td>IP20 (NEMA 2)</td> </tr> <tr> <td>Failsafe mode</td> <td>Short-circuit</td> </tr> <tr> <td>TECHNOLOGY</td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>1 pair</td> </tr> </tbody> </table>	Electrical Characteristics		Network	0-10 V analogic line, 12 V digital	Nominal line voltage	Un 12 V	Max. DC operating voltage	Uc 15 Vdc	Max. load current @25°C	IL 750 mA	Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max} 20 kA	Nominal Discharge Current <i>C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)</i>	I _n 10 kA	Nominal Discharge Current <i>C2 (1.2/50μs / 8/20μs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)</i>	I _n 10 kA	Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)</i>	Up 40 V	Protection Level <i>C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</i>	Up 650 V	Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)</i>	Up 650 V	Impulse current <i>D1 (10/350μs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C</i>	I _{imp} 2.5 kA	Line resistance ($\pm 10\%$)	1.5 Ohm	DATA SPD TYPE	UL497B LISTED	VOLTS	(V) 6	WIRES	2W+Shield+G	LINE CURRENT MAX	(A) 0.3	AMBIENT MIN	(C) -50	AMBIENT MAX	(C) +85	RESIDUAL VOLTAGE	(V) 20	MCOV	(V) 8/72/72	IN <i>10 impulses 8/20μs</i>	(kA) 5	IMAX <i>8/20μs</i>	(kA) 10	I _{imp} <i>10/350μs</i>	(kA) 2.5	DATA SPEED	(Mbps) up to 10MHz	FREQUENCY	(MHz) up to 10	INSERTION LOSS (@ FREQ)	(db) < 1	Mechanical Characteristics		Technology	GDT+TVS diode	Connection to Network	By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)	Format	DIN box	Operating temperature	Tu -40/+85°C	Ingress Protection rating	IP20 (NEMA 2)	Failsafe mode	Short-circuit	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	1 pair
Electrical Characteristics																																																																									
Network	0-10 V analogic line, 12 V digital																																																																								
Nominal line voltage	Un 12 V																																																																								
Max. DC operating voltage	Uc 15 Vdc																																																																								
Max. load current @25°C	IL 750 mA																																																																								
Max. discharge current <i>max. withstand @ 8/20 μs by pole</i>	I _{max} 20 kA																																																																								
Nominal Discharge Current <i>C2 (1.2/50μs / 8/20μs), 10 applications, X-X (Line/Line), X-SG (Line/Signal Ground)</i>	I _n 10 kA																																																																								
Nominal Discharge Current <i>C2 (1.2/50μs / 8/20μs), 10 applications, X-C (Line/Earth), SG-C (Signal Ground/Earth)</i>	I _n 10 kA																																																																								
Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-Y (Line-Line), Y-SG (Line-Signal Ground)</i>	Up 40 V																																																																								
Protection Level <i>C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</i>	Up 650 V																																																																								
Protection Level <i>C3 (10/1000μs), 300 applications@10 A, Y-C (Line-Earth), SG-C (Signal Ground-Earth)</i>	Up 650 V																																																																								
Impulse current <i>D1 (10/350μs), 2 applications, X-C (Line/Earth), X-SG (Line/Signal Ground) and SG-C</i>	I _{imp} 2.5 kA																																																																								
Line resistance ($\pm 10\%$)	1.5 Ohm																																																																								
DATA SPD TYPE	UL497B LISTED																																																																								
VOLTS	(V) 6																																																																								
WIRES	2W+Shield+G																																																																								
LINE CURRENT MAX	(A) 0.3																																																																								
AMBIENT MIN	(C) -50																																																																								
AMBIENT MAX	(C) +85																																																																								
RESIDUAL VOLTAGE	(V) 20																																																																								
MCOV	(V) 8/72/72																																																																								
IN <i>10 impulses 8/20μs</i>	(kA) 5																																																																								
IMAX <i>8/20μs</i>	(kA) 10																																																																								
I _{imp} <i>10/350μs</i>	(kA) 2.5																																																																								
DATA SPEED	(Mbps) up to 10MHz																																																																								
FREQUENCY	(MHz) up to 10																																																																								
INSERTION LOSS (@ FREQ)	(db) < 1																																																																								
Mechanical Characteristics																																																																									
Technology	GDT+TVS diode																																																																								
Connection to Network	By spring terminal - max. cross section 2.5mm ² / AWG 13 (solid or stranded)																																																																								
Format	DIN box																																																																								
Operating temperature	Tu -40/+85°C																																																																								
Ingress Protection rating	IP20 (NEMA 2)																																																																								
Failsafe mode	Short-circuit																																																																								
TECHNOLOGY	SAD-GDT																																																																								
NETWORK CONFIGURATION	1 pair																																																																								
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode SG: Signal ground</p>																																																																									



CITEL

UL497B LISTED - I_{max} 20kA - In 5kA - Modular

DLA-12D3G

CONNECTION METHOD	Screw Terminal
MOUNTING	Din Rail
MATERIAL	Thermoplastic UL94-V0
NEMA RATING (IP RATING)	NEMA 2 (IP20)
DIMENSIONS	See diagram
WEIGHT	0.30 lbs
Standards	
UL STANDARD	UL497B
UL CATEGORY	QVGQ
UL FILE NUMBER	E184939
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS	ROHS
Part number	
640192	

