



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x 8/20 μ s)
- ↳ 5kA I_{mp} (2x 10/350 μ s)
- ↳ 5kA I_n (10x 8/20 μ s)
- ↳ Modular
- ↳ 2W+SHIELD+G

	Electrical Characteristics																																																																			
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube L: Inductor D: Clamping diode</p>	<table border="1"> <tr><td>Network</td><td></td><td>4-20 mA, 24 V analogic</td></tr> <tr><td>Max. DC operating voltage</td><td>Uc</td><td>28 Vdc</td></tr> <tr><td>Max. frequency</td><td>f max.</td><td>> 3 MHz</td></tr> <tr><td>Insertion loss</td><td></td><td>< 1 dB</td></tr> <tr><td>Max. load current @25°C</td><td>IL</td><td>2.4 A</td></tr> <tr><td>Protection Level C3 (10/1000μs), 300 applications@10 A, X-X (Line/Line)</td><td>Up</td><td>40 V</td></tr> <tr><td>Protection level C3 (10/1000μs), 300 applications@10 A, X-C (Line/Earth)</td><td>Up</td><td>40 V</td></tr> <tr><td>Impulse current 2 x 10/350μs Test - D1 Category</td><td>I_{imp}</td><td>5 kA</td></tr> <tr><td>Nominal Discharge Current, X-C (Line/Earth) 8/20μs Test x 10 - C2 Category</td><td>I_n L/PE</td><td>5 kA</td></tr> <tr><td>DATA SPD TYPE</td><td></td><td>UL497B LISTED</td></tr> <tr><td>VOLTS</td><td>(V)</td><td>24</td></tr> <tr><td>WIRES</td><td></td><td>2W+SHIELD+G</td></tr> <tr><td>LINE CURRENT MAX</td><td>(A)</td><td>2.4</td></tr> <tr><td>AMBIENT MIN</td><td>(C)</td><td>-50</td></tr> <tr><td>AMBIENT MAX</td><td>(C)</td><td>+85</td></tr> <tr><td>RESIDUAL VOLTAGE</td><td>(V)</td><td>40</td></tr> <tr><td>MCOV</td><td>(V)</td><td>28</td></tr> <tr><td>IN 10 impulses 8/20μs</td><td>(kA)</td><td>5</td></tr> <tr><td>IMAX 8/20μs</td><td>(kA)</td><td>20</td></tr> <tr><td>I_{imp} 10/350μs</td><td>(kA)</td><td>5</td></tr> <tr><td>DATA SPEED</td><td>(Mbps)</td><td>10/100</td></tr> <tr><td>INSERTION LOSS (@ FREQ)</td><td>(db)</td><td>< 1</td></tr> </table>		Network		4-20 mA, 24 V analogic	Max. DC operating voltage	Uc	28 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	2.4 A	Protection Level C3 (10/1000 μ s), 300 applications@10 A, X-X (Line/Line)	Up	40 V	Protection level C3 (10/1000 μ s), 300 applications@10 A, X-C (Line/Earth)	Up	40 V	Impulse current 2 x 10/350 μ s Test - D1 Category	I _{imp}	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20 μ s Test x 10 - C2 Category	I _n L/PE	5 kA	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	24	WIRES		2W+SHIELD+G	LINE CURRENT MAX	(A)	2.4	AMBIENT MIN	(C)	-50	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	40	MCOV	(V)	28	IN 10 impulses 8/20 μ s	(kA)	5	IMAX 8/20 μ s	(kA)	20	I _{imp} 10/350 μ s	(kA)	5	DATA SPEED	(Mbps)	10/100	INSERTION LOSS (@ FREQ)	(db)	< 1
Network		4-20 mA, 24 V analogic																																																																		
Max. DC operating voltage	Uc	28 Vdc																																																																		
Max. frequency	f max.	> 3 MHz																																																																		
Insertion loss		< 1 dB																																																																		
Max. load current @25°C	IL	2.4 A																																																																		
Protection Level C3 (10/1000 μ s), 300 applications@10 A, X-X (Line/Line)	Up	40 V																																																																		
Protection level C3 (10/1000 μ s), 300 applications@10 A, X-C (Line/Earth)	Up	40 V																																																																		
Impulse current 2 x 10/350 μ s Test - D1 Category	I _{imp}	5 kA																																																																		
Nominal Discharge Current, X-C (Line/Earth) 8/20 μ s Test x 10 - C2 Category	I _n L/PE	5 kA																																																																		
DATA SPD TYPE		UL497B LISTED																																																																		
VOLTS	(V)	24																																																																		
WIRES		2W+SHIELD+G																																																																		
LINE CURRENT MAX	(A)	2.4																																																																		
AMBIENT MIN	(C)	-50																																																																		
AMBIENT MAX	(C)	+85																																																																		
RESIDUAL VOLTAGE	(V)	40																																																																		
MCOV	(V)	28																																																																		
IN 10 impulses 8/20 μ s	(kA)	5																																																																		
IMAX 8/20 μ s	(kA)	20																																																																		
I _{imp} 10/350 μ s	(kA)	5																																																																		
DATA SPEED	(Mbps)	10/100																																																																		
INSERTION LOSS (@ FREQ)	(db)	< 1																																																																		
Mechanical Characteristics																																																																				
	<table border="1"> <tr><td>Technology</td><td></td><td>GDT+TVS diode</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminal: cross section 0.4-1.5mm²</td></tr> <tr><td>Format</td><td></td><td>Plug-in DIN box</td></tr> <tr><td>Failsafe mode</td><td></td><td>Short-circuit</td></tr> <tr><td>TECHNOLOGY</td><td></td><td>SAD-GDT</td></tr> <tr><td>NETWORK CONFIGURATION</td><td></td><td>1 pair</td></tr> <tr><td>CONNECTION METHOD</td><td></td><td>Screw Terminal</td></tr> <tr><td>MOUNTING</td><td></td><td>DIN RAIL</td></tr> <tr><td>MATERIAL</td><td></td><td>Thermoplastic UL94-V0</td></tr> <tr><td>NEMA RATING (IP RATING)</td><td></td><td>NEMA 2 (IP20)</td></tr> <tr><td>DIMENSIONS</td><td></td><td>See diagram</td></tr> <tr><td>WEIGHT</td><td></td><td>0.30 lbs</td></tr> <tr><td>SPARE PART</td><td></td><td>DLAM-24D3</td></tr> </table>		Technology		GDT+TVS diode	Connection to Network		By screw terminal: cross section 0.4-1.5mm ²	Format		Plug-in DIN box	Failsafe mode		Short-circuit	TECHNOLOGY		SAD-GDT	NETWORK CONFIGURATION		1 pair	CONNECTION METHOD		Screw Terminal	MOUNTING		DIN RAIL	MATERIAL		Thermoplastic UL94-V0	NEMA RATING (IP RATING)		NEMA 2 (IP20)	DIMENSIONS		See diagram	WEIGHT		0.30 lbs	SPARE PART		DLAM-24D3																											
Technology		GDT+TVS diode																																																																		
Connection to Network		By screw terminal: cross section 0.4-1.5mm ²																																																																		
Format		Plug-in DIN box																																																																		
Failsafe mode		Short-circuit																																																																		
TECHNOLOGY		SAD-GDT																																																																		
NETWORK CONFIGURATION		1 pair																																																																		
CONNECTION METHOD		Screw Terminal																																																																		
MOUNTING		DIN RAIL																																																																		
MATERIAL		Thermoplastic UL94-V0																																																																		
NEMA RATING (IP RATING)		NEMA 2 (IP20)																																																																		
DIMENSIONS		See diagram																																																																		
WEIGHT		0.30 lbs																																																																		
SPARE PART		DLAM-24D3																																																																		
Standards																																																																				
	<table border="1"> <tr><td>UL STANDARD</td><td></td><td>UL497B</td></tr> <tr><td>UL CATEGORY</td><td></td><td>QVGQ</td></tr> <tr><td>UL FILE NUMBER</td><td></td><td>E184939</td></tr> <tr><td>STANDARDS</td><td></td><td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td></tr> <tr><td>ENVIRONMENTAL STANDARDS</td><td></td><td>ROHS</td></tr> </table>		UL STANDARD		UL497B	UL CATEGORY		QVGQ	UL FILE NUMBER		E184939	STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS		ROHS																																																			
UL STANDARD		UL497B																																																																		
UL CATEGORY		QVGQ																																																																		
UL FILE NUMBER		E184939																																																																		
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																																		
ENVIRONMENTAL STANDARDS		ROHS																																																																		
Part number																																																																				
641003																																																																				

