




- ↳ 1 Pair Protection
- ↳ Modes of Protection L-L,L-G
- ↳ Conduit Mounting-1/2 inch NPT
- ↳ Direct Transducer Mount
- ↳ Parallel or Series Connection Options



Características eléctricas		
TENSION	(V)	48
MAXIMUM LINE VOLTAGE	(V)	54
WIRES		4W+GROUND
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-55
AMBIENT MAX	(C)	+85
PROTECTION LEVEL	(V)	82
IN	(kA)	10
IMAX	(kA)	15
Instalación		
Operating Relative Humidity	%RH	Can be submerged
Operating Altitude	Ft	2000.0000
Operating Altitude	Ft	6500.0000
Housing/Enclosure material		Stainless Steel
Mounting		Conduit-1/2" NPT
Installation Location		Indoor / outdoor
Product Dimension	mm	114.3000
Product Dimension	mm	26.0000
Product Dimension	mm	27.9400
Product Dimension	In	4.5000
Product Dimension	In	1.0000
Product Dimension	In	1.1000
Product Weight	lbs	0.8000
Miscelánea		
Individual Pack		Yes
Características mecánicas		
FORMA DE CONEXION		Series- #16 AWG Copper Wires-Tinned
Código		
6339		