

MSB10-400 with 6" lead



- ✦ MOV Technology
- ✦ I_{max} 18kA
- ✦ I_n 3kA
- ✦ LED Indicator
- ✦ IP67
- ✦ ANSI/IEEE C136.2 Extreme 20kV/10kA
- ✦ ANSI/IEEE C62.41 20kV/10kA
- ✦ UL Type 4CA
- ✦ 10-year warranty



Características eléctricas		
Red		230 V monofásica
Modo(s) de protección		Modo Común o Mode Diferenciado
Nivel de protección L/N @ I _n (8/20µs)	Up L/N	1.2 kV
POWER SPD TYPE		UL1449 5th Ed. TYPE 4CA
TENSION	(V)	277
AC/DC/DC PV/RF		AC
FASE	(PH)	1
AMPS	(A)	N/A
AMBIENT MIN	(C)	-35
AMBIENT MAX	(C)	+85
MODOS		L-L, L-G, L-N
MLV	(V)	780/1340/1330/-
MCOV	(V)	300/300/300
IN	(kA)	3
I _{cc} cortocircuito	(kA)	n/a
IMAX	(kA)	18
Instalación		
Operating Temperature	°C	-40.0000
Operating Temperature	°C	85.0000
Operating Temperature	°F	-40.0000
Operating Temperature	°F	85.0000
Operating Relative Humidity	%RH	95
Operating Altitude	Ft	2000.0000
Operating Altitude	Ft	6500.0000
Housing/Enclosure material		Thermoplastic
Flammability rating		V0
Mounting		WALL MOUNT
IP Environmental rating		IP20
Installation Location		indoor
Product Dimension	mm	60.0000
Product Dimension	mm	24.0000
Product Dimension	mm	40.0000
Product Dimension	In	2.3600
Product Dimension	In	0.9400
Product Dimension	In	1.5700
Miscelánea		
Individual Pack		Yes
Storage Temperature	°C	-40.0000
Storage Temperature	°C	85.0000
Storage Temperature	°F	-40.0000
Storage Temperature	°F	85.0000
Características mecánicas		
Tecnología		MOV
Conexión a la red		Salida por hilos
Modo de fallo		Desconexión de la red Baja Tensión
TECNOLOGIA		Thermal-MOV
CONFIGURACION DE RED		1PH, 2W+G, Single Phase (or 2PH, 2W+G, Two Phase)
FORMA DE CONEXION		6" #14 AWG LEADS
MONTAJE		FLANGE MOUNT
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 6P (IP67)
DESCONEXION SEGURA		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		LED Indicator
DIMENSIONS		See diagram
WEIGHT		0.30 lbs
SPARE PART		n/a
Normas		

MSB10-400 with 6" lead

Certificación	UL / TUV
UL STANDARD	UL1449 5th Edition
UL CATEGORY	VZCA2, VZCA8
UL FILE NUMBER	E326289
NORMAS	NOM-003-SCFI-2014, NOM-001-SCFI-1993
ANSI/IEEE C62.41	Category C 20kV/10kA
ENVIRONMENTAL STANDARDS	ROHS
Código	
5615011	