



CITEL

B180-12D3



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max}
- ↳ 5kA I_{imp}
- ↳ 5kA I_n



	<table border="1"> <thead> <tr> <th colspan="2">Electrical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Network</td> <td>RS232, RS485</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>U_c 15 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max. > 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td>< 1 dB</td> </tr> <tr> <td>Protection mode(s)</td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)</td> <td>U_p 30 V</td> </tr> <tr> <td>Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)</td> <td>U_p 20 V</td> </tr> <tr> <td>DATA SPD TYPE</td> <td>UL497B LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V) 12</td> </tr> <tr> <td>WIRES</td> <td>2W+GROUND</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A) 0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C) -50</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C) +85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V) 30</td> </tr> <tr> <td>MCOV</td> <td>(V) 15/72/72</td> </tr> <tr> <td>I_N 10 impulses 8/20µs</td> <td>(kA) 5</td> </tr> <tr> <td>I_{MAX} 8/20µs</td> <td>(kA) 20</td> </tr> <tr> <td>I_{imp} 10/350µs</td> <td>(kA) 5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps) up to 10MHz</td> </tr> </tbody> </table>	Electrical Characteristics		Network	RS232, RS485	Max. DC operating voltage	U _c 15 Vdc	Max. frequency	f max. > 3 MHz	Insertion loss	< 1 dB	Protection mode(s)	Common/Differential mode	Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	U _p 30 V	Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	U _p 20 V	DATA SPD TYPE	UL497B LISTED	VOLTS	(V) 12	WIRES	2W+GROUND	LINE CURRENT MAX	(A) 0.3	AMBIENT MIN	(C) -50	AMBIENT MAX	(C) +85	RESIDUAL VOLTAGE	(V) 30	MCOV	(V) 15/72/72	I _N 10 impulses 8/20µs	(kA) 5	I _{MAX} 8/20µs	(kA) 20	I _{imp} 10/350µs	(kA) 5	DATA SPEED	(Mbps) up to 10MHz						
Electrical Characteristics																																															
Network	RS232, RS485																																														
Max. DC operating voltage	U _c 15 Vdc																																														
Max. frequency	f max. > 3 MHz																																														
Insertion loss	< 1 dB																																														
Protection mode(s)	Common/Differential mode																																														
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	U _p 30 V																																														
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	U _p 20 V																																														
DATA SPD TYPE	UL497B LISTED																																														
VOLTS	(V) 12																																														
WIRES	2W+GROUND																																														
LINE CURRENT MAX	(A) 0.3																																														
AMBIENT MIN	(C) -50																																														
AMBIENT MAX	(C) +85																																														
RESIDUAL VOLTAGE	(V) 30																																														
MCOV	(V) 15/72/72																																														
I _N 10 impulses 8/20µs	(kA) 5																																														
I _{MAX} 8/20µs	(kA) 20																																														
I _{imp} 10/350µs	(kA) 5																																														
DATA SPEED	(Mbps) up to 10MHz																																														
<p>G: 3-electrode gas tube R: Resistor D3: 3-pole clamping diode</p>	<table border="1"> <thead> <tr> <th colspan="2">Mechanical Characteristics</th> </tr> </thead> <tbody> <tr> <td>Technology</td> <td>GDT+TVS diode</td> </tr> <tr> <td>Connection to Network</td> <td>By screw terminal: cross section 0.4-1.5mm²</td> </tr> <tr> <td>Format</td> <td>Wall mounting box</td> </tr> <tr> <td>Failsafe mode</td> <td>Short-circuit - transmission cut-off - fault mode 2</td> </tr> <tr> <td>TECHNOLOGY</td> <td>SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td>2W+G</td> </tr> <tr> <td>CONNECTION METHOD</td> <td>RJ11 Connector</td> </tr> <tr> <td>MOUNTING</td> <td>Wall mount</td> </tr> <tr> <td>MATERIAL</td> <td>Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td>NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td>See diagram</td> </tr> <tr> <td>WEIGHT</td> <td>0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td>n/a</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">Standards</th> </tr> </thead> <tbody> <tr> <td>Certification</td> <td>UL 497B</td> </tr> <tr> <td>UL STANDARD</td> <td>UL497B</td> </tr> <tr> <td>UL CATEGORY</td> <td>QVGG</td> </tr> <tr> <td>UL FILE NUMBER</td> <td>E184939</td> </tr> <tr> <td>STANDARDS</td> <td>IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td>ROHS</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="2">Part number</th> </tr> </thead> <tbody> <tr> <td colspan="2">510202</td> </tr> </tbody> </table>	Mechanical Characteristics		Technology	GDT+TVS diode	Connection to Network	By screw terminal: cross section 0.4-1.5mm ²	Format	Wall mounting box	Failsafe mode	Short-circuit - transmission cut-off - fault mode 2	TECHNOLOGY	SAD-GDT	NETWORK CONFIGURATION	2W+G	CONNECTION METHOD	RJ11 Connector	MOUNTING	Wall mount	MATERIAL	Thermoplastic UL94-V0	NEMA RATING (IP RATING)	NEMA 2 (IP20)	DIMENSIONS	See diagram	WEIGHT	0.30 lbs	SPARE PART	n/a	Standards		Certification	UL 497B	UL STANDARD	UL497B	UL CATEGORY	QVGG	UL FILE NUMBER	E184939	STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993	ENVIRONMENTAL STANDARDS	ROHS	Part number		510202	
Mechanical Characteristics																																															
Technology	GDT+TVS diode																																														
Connection to Network	By screw terminal: cross section 0.4-1.5mm ²																																														
Format	Wall mounting box																																														
Failsafe mode	Short-circuit - transmission cut-off - fault mode 2																																														
TECHNOLOGY	SAD-GDT																																														
NETWORK CONFIGURATION	2W+G																																														
CONNECTION METHOD	RJ11 Connector																																														
MOUNTING	Wall mount																																														
MATERIAL	Thermoplastic UL94-V0																																														
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																														
DIMENSIONS	See diagram																																														
WEIGHT	0.30 lbs																																														
SPARE PART	n/a																																														
Standards																																															
Certification	UL 497B																																														
UL STANDARD	UL497B																																														
UL CATEGORY	QVGG																																														
UL FILE NUMBER	E184939																																														
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																														
ENVIRONMENTAL STANDARDS	ROHS																																														
Part number																																															
510202																																															

