





- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x 8/20us)
- ↳ 5kA I_{imp} (2x 10/350us)
- ↳ 10kA I_n (10x 8/20us)
- ↳ Modular
- ↳ 4W+SHIELD+G



Electrical Characteristics

Network		Telephone line, ADSL2, SHDSL, VDSL2
Max. DC operating voltage	U _c	170 Vdc
Max. frequency	f max.	> 10 MHz
Max. load current @25°C	I _L	300 mA
Protection Level C3 (10/1000µs), 300 applications@10 A, X-X (Line/Line)	U _p	220 V
Protection level C3 (10/1000µs), 300 applications@10 A, X-C (Line/Earth)	U _p	20 V
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA
Nominal discharge current C2 Category	I _n	5 kA
Line resistance (± 10%)		4.7 Ohm
DATA SPD TYPE		UL497B LISTED
VOLTS	(V)	150
WIRES		4W+SHIELD+GROUND
LINE CURRENT MAX	(A)	0.3
AMBIENT MIN	(C)	-50
AMBIENT MAX	(C)	+85
RESIDUAL VOLTAGE	(V)	210
MCOV	(V)	170
IMAX 8/20µs	(kA)	20
I _{imp} 10/350µs	(kA)	5
DATA SPEED	(Mbps)	up to 10MHz
FREQUENCY	(MHz)	up to 10
INSERTION LOSS (@ FREQ)	(db)	< 1
CAPACITANCE	(pF)	< 50



G: 3-electrode gas tube
 Gb: 2-electrode gas tube
 R: Resistor
 D: Clamping diode

Mechanical Characteristics

Technology		GDT+TVS diode
Connection to Network		By screw terminal: cross section 0.5-2.5mm ²
Format		Plug-in DIN box
Operating and storage temperature		-40/+85°C
Failsafe mode		Short-circuit
Weight		0.089 kg
TECHNOLOGY		SAD-GDT
NETWORK CONFIGURATION		2 Channel (4W+SHIELD+G)
CONNECTION METHOD		Screw Terminal
MOUNTING		Din Rail
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
DIMENSIONS		See diagram
WEIGHT		0.30 lbs
SPARE PART		DLA2M-170D3

Standards

Certification		UL Listed
UL STANDARD		UL497B
UL CATEGORY		QVGQ
UL FILE NUMBER		E184939
STANDARDS		IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS

Part number

640611

