



ULiQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Model(s): MDS750E-240Y*(d)

Permanently Connected

| <u>SPD Type</u> | <u>Volts (V)</u> | <u>AC/DC DC PV</u> | <u>Phase</u> | <u>Amps (A)</u> | <u>Ambient Min(°C)</u> | <u>Ambient Max(°C)</u> | <u>Mode</u> | <u>VPR (Vpk)</u> | <u>MCOV (V)</u> | <u>In (kA)</u> | <u>SCCR (kA)</u> |
|-----------------|------------------|--------------------|--------------|-----------------|------------------------|------------------------|-------------|------------------|-----------------|----------------|------------------|
| 2 | 415/240 | AC | 3Y | n/a | -35 | 85 | L-L | 2500 | 640 | 20 | 200 |
| | | | | | | | L-N | 1800 | 320 | | |
| | | | | | | | L-G | 1800 | 320 | | |
| | | | | | | | N-G | 1200 | 275 | | |

Evaluated to: UL 1449 4th Ed. Rev: 2016-03-17 and CSA C22.2 No. 269.2-13, 2013-06

(d) - May be followed by -H or -L.

* - Complementary Listed as EMI Filters.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report

Date: 2015-06-28

Last Revised: 2016-02-24

© 2018 UL LLC

