



ULiQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Model(s): MS200-240DCT, MS160-240DCT (e)

<u>SPD Type</u>	<u>Volts (V)</u>	<u>AC/DC DC PV</u>	<u>Phase</u>	<u>Amps (A)</u>	<u>Ambient Min(°C)</u>	<u>Ambient Max(°C)</u>	<u>Mode</u>	<u>VPR (Vpk)</u>	<u>MCOV (V)</u>	<u>In (kA)</u>	<u>SCCR (kA)</u>
1	120/240	AC	3H	-	-35	85	L-L	1000	300	20	200
							L-N	700	150		
							L-G	700	150		
							N-G	700	150		
							H-L	3000	470		
							H-N	700	320		
							H-G	700	320		

Evaluated to: UL 1449 4th Ed. Rev: 2016-03-17 and CSA C22.2 No. 269.1-14, 2014-11

(e) - may be followed by "-C", may be followed by "-H" or "-L" (C may be combined with H or L)

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report
Date: 2016-11-04
Last: 2016-11-10
Revised:

© 2018 UL LLC

