



# ULiQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

### Cat No(s): DS44S-320%

| SPD Type | Volts (V) | AC/DC DC PV | Phase | Amps (A) | Ambient Min(°C) | Ambient Max(°C) | Mode | VPR (Vpk) | MLV (Vpk) | MCOV (V) | Vn (Vdc) | In (kA) | SCCR (kA) | Notes |
|----------|-----------|-------------|-------|----------|-----------------|-----------------|------|-----------|-----------|----------|----------|---------|-----------|-------|
| 4CA (5)  | 415/240   | AC          | 3Y    | N/A      | -35             | 60              | L-L  | -         | 2930      | 600      | -        | 20      | N/A       | 2     |
|          |           |             |       |          |                 |                 | L-G  | -         | 1770      | 320      | N/A      |         |           |       |
| 4CA (5)  | 415/240   | AC          | 3Y    | N/A      | -35             | 60              | L-L  | -         | 2930      | 600      | -        | 10      | N/A       | 2     |
|          |           |             |       |          |                 |                 | L-G  | -         | 1770      | 320      | N/A      |         |           |       |

Evaluated to: UL 1449 4th Ed. Rev: 2016-03-17 and CSA Electrical Certification Notice 516/CSA C22.2 No. 8 13

% - May be followed by S

- - L-L modes may also be labeled as L-N modes

Note 2 - Suitable for Field and Factory wiring.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report

Date: 2010-02-25

Last 2016-04-18

Revised:

© 2018 UL LLC

