



UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DAC52VGUS-120S

<u>SPD</u> <u>Type</u>	<u>Volts</u> <u>(V)</u>	<u>AC/DC</u> <u>DC PV</u>	<u>Phase</u>	<u>Amps</u> <u>(A)</u>	<u>Ambient</u> <u>Min(°C)</u>	<u>Ambient</u> <u>Max(°C)</u>	<u>Mode</u>	<u>VPR</u> <u>(Vpk)</u>	<u>MLV</u> <u>(Vpk)</u>	<u>MCOV</u> <u>(V)</u>	<u>Vn</u> <u>(Vdc)</u>	<u>In</u> <u>(kA)</u>	<u>SCCR</u> <u>(kA)</u>	<u>Notes</u>
4CA	120	AC	1	n/a	-40	85	L-N	-	3320	150	n/a	20	n/a	2,5a
							L-G	-	3160	150	n/a			
							N-G	-	3080	150	n/a			

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 2 - Suitable for Field and Factory wiring.

Note 5a - Body of discrete component metal-oxide varistors (MOVs) flammability: Min. V-0 or VTM-0.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2021-05-25

Last Revised: 2021-09-30

© 2022 UL LLC

