



UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DAC52VGUS-120T/NN

| <u>SPD</u> Type | <u>Volts</u> (V) | <u>AC/DC</u> DC PV | <u>Phase</u> | <u>Amps</u> (A) | <u>Ambient</u> Min(°C) | <u>Ambient</u> Max(°C) | <u>Mode</u> | <u>VPR</u> (Vpk) | <u>MLV</u> (Vpk) | <u>MCOV</u> (V) | <u>Vn</u> (Vdc) | <u>In</u> (kA) | <u>SCCR</u> (kA) | <u>Notes</u> |
|--------------------|---------------------|-----------------------|--------------|--------------------|---------------------------|---------------------------|-------------|---------------------|---------------------|--------------------|--------------------|-------------------|---------------------|--------------|
| 4CA | 240/120 | AC | 1S | n/a | -40 | 85 | L-L | - | 5900 | 300 | n/a | 20 | n/a | 2,5a |
| | | | | | | | L-N | - | 2950 | 150 | n/a | | | |

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 2 - Suitable for Field and Factory wiring.

Note 5a - Body of discrete component metal-oxide varistors (MOVs) flammability: Min. V-0 or VTM-0.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2021-05-25

Last Revised: 2021-09-30

© 2022 UL LLC

