



# UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

**Cat No(s): DAC54VGUS-240Y**

| <u>SPD</u><br>Type | <u>Volts</u><br>(V) | <u>AC/DC</u><br>DC PV | <u>Phase</u> | <u>Amps</u><br>(A) | <u>Ambient</u><br>Min(°C) | <u>Ambient</u><br>Max(°C) | <u>Mode</u> | <u>VPR</u><br>(Vpk) | <u>MLV</u><br>(Vpk) | <u>MCOV</u><br>(V) | <u>Vn</u><br>(Vdc) | <u>In</u><br>(kA) | <u>SCCR</u><br>(kA) | <u>Notes</u> |
|--------------------|---------------------|-----------------------|--------------|--------------------|---------------------------|---------------------------|-------------|---------------------|---------------------|--------------------|--------------------|-------------------|---------------------|--------------|
| 4CA                | 415/240             | AC                    | 3Y           | n/a                | -40                       | 85                        | L-L         | -                   | 6580                | 610                | n/a                | 20                | n/a                 | 2,5a         |
|                    |                     |                       |              |                    |                           |                           | L-N         | -                   | 6580                | 305                | n/a                |                   |                     |              |
|                    |                     |                       |              |                    |                           |                           | L-G         | -                   | 3290                | 305                | n/a                |                   |                     |              |
|                    |                     |                       |              |                    |                           |                           | N-G         | -                   | 3260                | 305                | n/a                |                   |                     |              |

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 2 - Suitable for Field and Factory wiring.

Note 5a - Body of discrete component metal-oxide varistors (MOVs) flammability: Min. V-0 or VTM-0.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2021-05-25

Last Revised: 2021-09-30

© 2022 UL LLC

