



# UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

### Cat No(s): DS50PVS-800#

SPD Type	Volts (V)	AC/DC DC PV	Phase	Amps (A)	Ambient Min(°C)	Ambient Max(°C)	Mode	VPR (Vpk)	MLV (Vpk)	MCOV (V)	Vn (Vdc)	In (kA)	SCCR (kA)	Notes
4CA (5)	800	DC PV	-	n/a	-40	85	DC+-DC-	-	2920	840	n/a	20	-	1
							DC+-G	-	3170	840	n/a			
							DC--G	-	3170	840	n/a			

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08 and CSA C22.2 No. 269.5-17, 2017-09

# - may be suffixed with DE.

Note 1 - Suitable for Factory wiring only.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2011-02-05

Last Revised: 2021-09-30

© 2022 UL LLC

