



# UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

**Model(s): MS100-240Y(e), MS80-240Y(e)**

<u>SPD Type</u>	<u>Volts (V)</u>	<u>AC/DC DC PV</u>	<u>Phase</u>	<u>Amps (A)</u>	<u>Ambient Min(°C)</u>	<u>Ambient Max(°C)</u>	<u>Mode</u>	<u>VPR (Vpk)</u>	<u>MCOV (V)</u>	<u>In (kA)</u>	<u>SCCR (kA)</u>
1	240/415	AC	3Y	-	-35	85	L-L	1800	640	20	200
							L-N	1000	320		
							L-G	1200	320		
							N-G	1000	320		

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

(e) - may be followed by "-C", may be followed by "-H" or "-L" (C may be combined with H or L)

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2019-07-26

Last Revised: 2021-09-30

© 2022 UL LLC

