



# UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

**Citel America Inc**

10108 USA Today Way, Miramar FL 33025

**Model(s): DS73US-277Y/NN**

Open-Type SPD

<u>SPD Type</u>	<u>Volts (V)</u>	<u>AC/DC DC PV</u>	<u>Phase</u>	<u>Amps (A)</u>	<u>Ambient Min(°C)</u>	<u>Ambient Max(°C)</u>	<u>Mode</u>	<u>VPR (Vpk)</u>	<u>MCOV (V)</u>	<u>In (kA)</u>	<u>SCCR (kA)</u>
1	480/277	AC	3Y	n/a	-40	85	L-L L-G	2500 1500	840 420	20	200

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08 and CSA C22.2 No. 269.1-17, 2017-02

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2016-06-19

Last Revised: 2021-09-30

© 2022 UL LLC

