



# UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

## Citel America Inc

10108 USA Today Way, Miramar FL 33025

### Cat No(s): DS44S 320/G%

| <u>SPD</u><br><u>Type</u> | <u>Volts</u><br><u>(V)</u> | <u>AC/DC</u><br><u>DC PV</u> | <u>Phase</u> | <u>Amps</u><br><u>(A)</u> | <u>Ambient</u><br><u>Min(°C)</u> | <u>Ambient</u><br><u>Max(°C)</u> | <u>Mode</u> | <u>VPR</u><br><u>(Vpk)</u> | <u>MLV</u><br><u>(Vpk)</u> | <u>MCOV</u><br><u>(V)</u> | <u>Vn</u><br><u>(Vdc)</u> | <u>In</u><br><u>(kA)</u> | <u>SCCR</u><br><u>(kA)</u> | <u>Notes</u> |
|---------------------------|----------------------------|------------------------------|--------------|---------------------------|----------------------------------|----------------------------------|-------------|----------------------------|----------------------------|---------------------------|---------------------------|--------------------------|----------------------------|--------------|
| 4CA (5)                   | 415/240                    | AC                           | 3Y           | n/a                       | -40                              | 60                               | L-L         | -                          | 2720                       | 600                       | -                         | 20                       | n/a                        | 2            |
|                           |                            |                              |              |                           |                                  |                                  | L-N         | -                          | 1590                       | 320                       | n/a                       |                          |                            |              |
|                           |                            |                              |              |                           |                                  |                                  | L-G         | -                          | 2280                       | 320                       | -                         |                          |                            |              |
|                           |                            |                              |              |                           |                                  |                                  | N-G         | -                          | 1170                       | 255                       | -                         |                          |                            |              |

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08 and CSA C22.2 No. 269.5-17, 2017-09

% - May be followed by S

Note 2 - Suitable for Field and Factory wiring.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2010-02-25

Last Revised: 2021-09-30

© 2023 UL Solutions

