



UL iQ for Surge Protective Devices



Surge Protective Devices

E326289

Guide Information

Citel America Inc

10108 USA Today Way, Miramar FL 33025

Cat No(s): DS50VGPV-1000

SPD Type	Volts (V)	AC/DC DC PV	Phase	Amps (A)	Ambient Min(°C)	Ambient Max(°C)	Mode	VPR (Vpk)	MLV (Vpk)	MCOV (V)	Vn (Vdc)	In (kA)	SCCR (kA)	Notes
1CA	1000	DC PV	-	n/a	-40	75	DC+-DC-	4000	-	1200	-	20	50	1
							DC+-G	4000	-	1200	-			
							DC--G	4000	-	1200	-			

Evaluated to: UL 1449 5th Ed. Rev: 2021-01-08

Note 1 - Suitable for Factory wiring only.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.

Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2011-02-05

Last Revised: 2023-02-15

© 2023 UL Solutions

