
DS50VGPV-1000



- UL Type 1CA DC SPD
  - Designed with High Energy MOV's
  - Modular Design for Ease of Maintenance
  - Integrated Status Indicator Window
  - Imax : 40 kA /pole at 8/20µs
  - In : 20 kA /pole at 8/20µs
  - UL 1449 5th Edition Recognized

Electrical Characteristics		
Max. discharge current *max. withstand @ 8/20 µs by pole*	Imax	40 kA
Connection mode(s)		+/-/PE
Protection mode(s)		Common/Differential mode
POWER SPD TYPE		UL1449 TYPE 1CA
VOLTS	(V)	1000
AC/DC/DC PV/RF		DC PV
PHASE	(PH)	
AMPS	(A)	N/A
AMBIENT MIN	(C)	-40
AMBIENT MAX	(C)	+85
MODES		DC+-G or DC--G
MCOV	(V)	1000/1000/1000
IN *15 impulses 8/20µs*	(kA)	20
SCCR	(kA)	50
Mechanical Characteristics		
Technology		VG Technology (MOV+GSG)
Connection to Network		By screw terminals: 4-25mm²
Format		Plug-in modular box
Mounting		Symmetrical rail 35 mm (EN 60715)
Operating temperature	Tu	-40/+85°C
Protection rating		IP20
Failsafe mode		Disconnection SPD of the PV line
TECHNOLOGY		MOV+GSG
NETWORK CONFIGURATION		3 poles, 2W+G
CONNECTION METHOD		SPD-Screw Terminal (8-12AWG), Terminal blocks 6AWG
MOUNTING		Wall mount
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts
DIMENSIONS		See diagram
Standards		
Certification		UL
UL STANDARD		UL1449 5th Edition
UL FILE NUMBER		E326289
Part number		
480351		