



Electrical Characteristics		
Total Maximum discharge current max. total withstand @ 8 /20 $\mu$ s	I <sub>max</sub> Total	80 kA
Protection mode(s)		Common mode/Differential mode
POWER SPD TYPE		UL1449 TYPE 4CA
AC/DC/DC PV/RF		AC
AMPS	(A)	n/a
AMBIENT MIN	(C)	-40
AMBIENT MAX	(C)	+60
IN15 impulses 8/20 $\mu$ s	(kA)	20
SCCR	(kA)	n/a
IMAX8/20 $\mu$ s	(kA)	40
Iimp10/350 $\mu$ s	(kA)	4
Mechanical Characteristics		
Weight		0.19 kg
CONNECTION METHOD		Screw Terminal (8-12AWG)
MOUNTING		DIN RAIL
MATERIAL		Thermoplastic UL94-V0
NEMA RATING (IP RATING)		NEMA 2 (IP20)
FAIL-SAFE BEHAVIOR		Disconnection via fuse-link
REAL-TIME DIAGNOSTICS		Visual indicator and remote contacts
DIMENSIONS		See diagram (mm)
Standards		
Certification		UL / CSA / EAC / TUV
UL STANDARD		UL1449 5th Edition
UL CATEGORY		VZCA2, VZCA8
UL FILE NUMBER		E326289
STANDARDS		NOM-003-SCFI-2014, NOM-001-SCFI-1993
ENVIRONMENTAL STANDARDS		ROHS
Part number		
461121		