



↳ 19" Rack Mounted Sure Protection Panel

- 12, 24 or 48 Port Configurations
- Supports All Network Types
- RJ45 on Front and 110 Block on Rear
- Designed for Individual Port Replacement
- UL497B Listed

| Electrical Characteristics | | |
|---|---------|--|
| Network | | 100/1000/10G BaseT, RS422, RS485, RS423, Ethernet |
| Max. DC operating voltage | Uc | 7.5 Vdc |
| Max. frequency | f max. | 250 MHz |
| Max. data rate | | 10 Gbps |
| Insertion loss | | < 1 dB |
| Max. load current @25°C | IL | 750 mA |
| Max. capacitance | C | < 8 pF |
| Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category | In L/PE | 500 A |
| Capacity Maximum | pF | <8 |
| Telecom Discharge Current 10/1000 | kA | 0,1 |
| Telecom Total Discharge Current 10/1000 | kA | 0,1 |
| Telecom Discharge Current 10/1000 | kA | 0,1 |
| Telecom Discharge Current 10/1000 | kA | 0,1 |
| Option | | |
| RFI Filter | | no |
| Installation | | |
| Wiring type | | Shielded RJ45 |
| Operating Temperature _{Min} | °C | -40.0000 |
| Operating Temperature _{Max} | °C | 85.0000 |
| Operating Temperature _{Min} | °F | -40.0000 |
| Operating Temperature _{Max} | °F | 85.0000 |
| Operating Relative Humidity _{Max} | %RH | 95 |
| Operating Altitude _{Min} | Ft | 2000.0000 |
| Operating Altitude _{Max} | Ft | 6500.0000 |
| Housing/Enclosure material | | Aluminum |
| Mounting | | 19" Rack |
| IP Environmental rating _{IP} | | IP20 |
| NEMA Environmental rating _{NEMA} | | NEMA 1 |
| Installation Location | | Indoor |
| Product Dimension _H | mm | 89.0000 |
| Product Dimension _W | mm | 483.0000 |
| Product Dimension _H | In | 3.5000 |
| Product Dimension _W | In | 19.0000 |
| Miscellaneous | | |
| Individual Pack | | Yes |
| Storage Temperature _{Min} | °C | -40.0000 |
| Storage Temperature _{Max} | °C | 85.0000 |
| Storage Temperature _{Min} | °F | -40.0000 |
| Storage Temperature _{Max} | °F | 85.0000 |
| Storage Relative Humidity _{Max} | %RH | 95.0000 |
| Installation | | |
| Cable type | | Ethernet |
| Mechanical Characteristics | | |
| Technology | | Diode écrêtage |
| Connection to Network | | Self-stripping connector 110 back/RJ45 Female. front |
| Format | | Rack 19" |
| Failsafe mode | | Short-circuit |
| Pinout | | (1-2)(3-6)(4-5)(7-8) |
| Weight | | 0.3 kg |
| Part number | | |
| 6249 | | |